# Safety Data Sheet



### 1. Identification

Product Information: M545-2277

Product Name: WIPING WOOD STAIN DARK RED MAHOGANY GAL

Recommended Use: Surface Preparation or Protection

Supplied by: Mohawk Finishing Products

Division of RPM Industrial Coatings Group

2220 US Hwy 70 SE Suite 100

Hickory, NC 28602

USA

Company Phone No: (800) 522-8266

Emergency Phone No. CHEMTREC: (800) 424-9300

International Emergency No. CHEMTREC: (703) 527-3887 (Collect calls are accepted)

### 2. Hazards Identification

### **GHS Classification**

Acute Tox. 4 Inhalation, Carc. 1B, Eye Irrit. 2A, Flam. Liq. 3, Muta. 1B, Skin Irrit. 2, Skin Sens. 1

#### Symbol(s) of Product







Signal Word Danger

#### **GHS HAZARD STATEMENTS**

| Flammable Liquid, category 3           | H226 | Flammable liquid and vapour.         |
|--|------|--------------------------------------|
| Skin Irritation, category 2            | H315 | Causes skin irritation.              |
| Skin Sensitizer, category 1            | H317 | May cause an allergic skin reaction. |
| Eye Irritation, category 2A            | H319 | Causes serious eye irritation.       |
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled.                  |
| Germ Cell Mutagenicity, category 1B    | H340 | May cause genetic defects.           |
| Carcinogenicity, category 1B           | H350 | May cause cancer.                    |

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P405 Store locked up.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

P201 Obtain special instructions before use.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

# 3. Composition/Information on ingredients

| Chemical Name          | CAS-No.    | <u>Wt. %</u> | GHS Symbols    | GHS Statements               |
|------------------------|------------|--------------|----------------|------------------------------|
| aromatic hydrocarbons  | 64742-95-6 | 25-40        | GHS06-GHS08    | H304-331-340-350             |
| 1,2,4-trimethylbenzene | 95-63-6    | 10-25        | GHS02-GHS07    | H226-315-319-332-335         |
| aromatic hydrocarbons  | 64742-94-5 | 2.5-10       | GHS07-GHS08    | H304-332                     |
| petroleum distillate   | 64742-48-9 | 2.5-10       | GHS08          | H304-340-350                 |
| naphthalene            | 91-20-3    | 0.1-1.0      | GHS06-GHS08    | H302-312-330-351             |
| carbon black           | 1333-86-4  | 0.1-1.0      | GHS02          | H251                         |
| cumene                 | 98-82-8    | 0.1-1.0      | GHS02-GHS07-   | H226-302-304-332-335         |
|                        |            |              | GHS08          |                              |
| crystalline silica     | 14808-60-7 | 0.1-1.0      | No Information | No Information               |
| n-butyl acetate        | 123-86-4   | 0.1-1.0      | GHS02-GHS07    | H226-336                     |
| methyl ethyl ketoxime  | 96-29-7    | 0.1-1.0      | GHS05-GHS06-   | H302-311-315-317-318-331-336 |
| • •                    |            |              | GHS07-GHS08    | -350-370-373                 |

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

#### 4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention.

FIRST AID - INGESTION: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

# 5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

### Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

# 7. Handling and Storage





**HANDLING:** Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

### 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

| Chemical Name          | ACGIH TLV-TWA | ACGIH-TLV STEL | OSHA PEL-TWA | OSHA PEL-CEILING |
|------------------------|---------------|----------------|--------------|------------------|
| aromatic hydrocarbons  | N.D.          | N.D.           | N.D.         | N.D.             |
| 1,2,4-trimethylbenzene | 10 ppm        | N.D.           | N.D.         | N.D.             |
| aromatic hydrocarbons  | N.D.          | N.D.           | N.D.         | N.D.             |
| petroleum distillate   | N.D.          | N.D.           | N.D.         | N.D.             |
| naphthalene            | 10 ppm        | N.D.           | 10 ppm       | N.D.             |
| carbon black           | 3 mg/m3       | N.D.           | 3.5 mg/m3    | N.D.             |
| cumene                 | 5 ppm         | N.D.           | 50 ppm       | N.D.             |
| crystalline silica     | 0.025 mg/m3   | N.D.           | 50 μg/m3     | N.D.             |
| n-butyl acetate        | 50 ppm        | 150 ppm        | 150 ppm      | N.D.             |
| methyl ethyl ketoxime  | N.D.          | N.D.           | N.D.         | N.D.             |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

#### **Personal Protection**



**RESPIRATORY PROTECTION:** Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.



**SKIN PROTECTION:** Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



**EYE PROTECTION:** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



OTHER PROTECTIVE EQUIPMENT: No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

# 9. Physical and Chemical Properties

Appearance: Colored Liquid Physical State: LIQUID

Odor: Oily Hydrocarbon Odor Threshold: Not determined

Density, g/cm3: 0.993 pH: Not determined

Freeze Point, °F:

Solubility in Water:

Not determined

Not determined

Not determined

Not determined

Not determined

Decomposition temperature, °F: Not determined water:

Not determined water:

Not determined Explosive Limits, %:

Not determined

**Boiling Range, °F**: > 100 °F **Flash Point, °F**: 106 ° F

Combustibility:Supports CombustionAuto-Ignition Temperature, °F:Not determinedEvaporation Rate:Faster than Diethyl EtherVapor Pressure, mmHg:Not determined

Vapor Density: Not determined

N.I. = No Information

# 10. Stability and reactivity

STABILITY: Stable under normal conditions.

**CONDITIONS TO AVOID:** Heat, flames and sparks. **INCOMPATIBILITY:** Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

# 11. Toxicological information



# **Practical Experiences**

**EMERGENCY OVERVIEW:** No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

**EFFECT OF OVEREXPOSURE - INHALATION: No Information** 

**EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information** 

**CARCINOGENICITY:** May cause cancer.

PRIMARY ROUTE(S) OF ENTRY:

Eye Contact, Skin Contact, Inhalation

### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

| <u>CAS-No.</u><br>64742-95-6 | <u>Chemical Name</u><br>aromatic hydrocarbons | Oral LD50<br>14000 mg/kg Rat | Dermal LD50<br>>2000 mg/kg Rabbit | <u>Vapor LC50</u><br>>4.96 mg/l Rat |
|------------------------------|---|------------------------------|-----------------------------------|-------------------------------------|
| 95-63-6                      | 1,2,4-trimethylbenzene                        | 3280 mg/kg Rat               | >3160 mg/kg Rabbit                | 18 mg/L Rat                         |
| 64742-94-5                   | aromatic hydrocarbons                         | >6000 mg/kg Rat              | >3160 mg/kg Rabbit                | >17.1 mg/L Rat                      |
| 64742-48-9                   | petroleum distillate                          | >5000 mg/kg Rat              | >3160 mg/kg Rabbit                | >20 mg/L Rat                        |
| 91-20-3                      | naphthalene                                   | 1110 mg/kg Rat               | 1120 mg/kg Rabbit                 | >0.4 mg/L Rat                       |
| 1333-86-4                    | carbon black                                  | >5000 mg/kg Rat              | >3000 mg/kg Rabbit                | >20 mg/l                            |
| 98-82-8                      | cumene  | 1400 mg/kg Rat               | 10603 mg/kg Rabbit                | >20 mg/l                            |
| 14808-60-7                   | crystalline silica                            | >5000 mg/kg                  | >5000 mg/kg                       | >20 mg/l Rat                        |
| 123-86-4                     | n-butyl acetate                               | 14130 mg/kg Rat              | >17600 mg/kg Rabbit               | 23.4 mg/l Rat                       |
| 96-29-7                      | methyl ethyl ketoxime                         | 930 mg/kg Rat                | 1000 mg/kg Rabbit                 | >4.83 mg/L Rat                      |

#### N.I. = No Information

### 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

### 13. Disposal Information



#### **Product**

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

# Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT: COMBUSTIBLE - NOT RESTRICTED GROUND

IATA: UN1263, PAINT, 3, III

UN1263, PAINT, 3, III IMDG:

# 15. Regulatory Information

# U.S. Federal Regulations:

# **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u>   | <u>CAS-No.</u> | <u>Wt. %</u> |  |
|------------------------|----------------|--------------|--|
| 1,2,4-trimethylbenzene | 95-63-6        | 17.91        |  |
| naphthalene            | 91-20-3        | 0.94         |  |

#### TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA components exist in this product.

# U.S. State Regulations:

### **CALIFORNIA PROPOSITION 65**



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Naphthalene, Cancer, 0.9429% Toluene, Reproductive Harm, 0.0001%

#### **NOTICE**

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

# 16. Other Information

**Revision Date:** 6/14/2023 **Supersedes Date:** 3/17/2023

Reason for revision: Substance and/or Product Properties Changed in Section(s):

08 - Exposure Controls/Personal Protection

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

H370

| Health: | 2 | Flammability: | 2 | Reactivity: | 0 | Personal Protection: | Χ |
|---------|---|---------------|---|-------------|---|----------------------|---|
|---------|---|---------------|---|-------------|---|----------------------|---|

### Volatile Organic Compounds, gr/ltr: 731

# Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| H226 | Flammable liquid and vapour.                  |
|------|---|
| H251 | Self-heating: may catch fire.                 |
| H302 | Harmful if swallowed.                         |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin.                   |
| H312 | Harmful in contact with skin.                 |
| H315 | Causes skin irritation.                       |
| H317 | May cause an allergic skin reaction.          |
| H318 | Causes serious eye damage.                    |
| H319 | Causes serious eye irritation.                |
| H330 | Fatal if inhaled.                             |
| H331 | Toxic if inhaled.                             |
| H332 | Harmful if inhaled.                           |
| H335 | May cause respiratory irritation.             |
| H336 | May cause drowsiness or dizziness.            |
| H340 | May cause genetic defects.                    |
| H350 | May cause cancer.                             |
| H351 | Suspected of causing cancer.                  |

H373 May cause damage to organs through prolonged or repeated exposure.

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:

Causes damage to organs.



The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.