

CAB AEROSOL PLATINUM

PRODUCT NUMBER

DESCRIPTION

M104-4443

CAB AEROSOL PLATINUM

PRODUCT DESCRIPTION:

TECHNICAL DATA SHEET

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology N/A Color SILVER Sheen N/A Viscosity N/A WPG 6.604284094 lbs/gal Solids by Volume 6.634419547 ±1% Solids by Weight 10.191948901 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.52886144 g/l Material VOC (b/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Retarder N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A		
Sheen N/A Viscosity N/A WPG 6.604284094 lbs/gal Solids by Volume 6.634419547 ±1% Solids by Weight 10.191948901 ±1% Flash Point -76.000000000°F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.528886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Technology	N/A
Viscosity N/A WPG 6.604284094 lbs/gal Solids by Volume 6.634419547 ±1% Solids by Weight 10.191948901 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.528886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Color	SILVER
WPG 6.604284094 lbs/gal Solids by Volume 6.634419547 ±1% Solids by Weight 10.191948901 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.52886144 g/l Material VOC (tb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Sheen	N/A
Solids by Volume 6.634419547 ±1% Solids by Weight 10.191948901 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.528886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Viscosity	N/A
Solids by Weight 10.191948901 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.52886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	WPG	6.604284094 lbs/gal
Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.528886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Volume	6.634419547 ±1%
HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.528886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Weight	10.191948901 ±1%
Coating VOC (g/l) 704.103216898 g/l Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.528886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Flash Point	-76.000000000 °F
Coating VOC (Lb/Gal) 5.876047076 lbs/gal Material VOC (g/l) 655.528886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	HMIS	H: 2, F: 4, R: 0, P: X
Material VOC (g/l) 655.528886144 g/l Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (g/I)	704.103216898 g/l
Material VOC (Lb/Gal) 5.470673194 lbs/gal #VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (Lb/Gal)	5.876047076 lbs/gal
#VOC/#Solid 8.127515143 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (g/l)	655.528886144 g/l
VHAP Ratio (#VHAP/#Solid) 0.626771091 Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (Lb/Gal)	5.470673194 lbs/gal
Spread Rate 106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	#VOC/#Solid	8.127515143 lbs/lbs solid
Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	VHAP Ratio (#VHAP/#Solid)	0.626771091
Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Spread Rate	106.416089534 sq. ft./gal @ 1.0 mil DFT (no loss)
Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Catalyst/Ratio	N/A
AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Reducer	N/A
Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Retarder	N/A
Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	36 months
	Pot-Life (Catalyzed)	N/A
DII NIA	Recoat Instruction	N/A
PH N/A	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.