

# Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Ultra Classic™ Toner (13 oz. aerosols)

M100 - color number (25 colors available)

**Product Description:** Mohawk Ultra Classic™ Toners have proven themselves very successful throughout the Touch-up industry where extreme transparency and clarity is required. Fade resistant and non-bleeding dyes are used for the entire color line. These toners can be used from making small touch-up repairs to shading and toning an entire article. Use the appropriate clear lacquer aerosol if the sheen level needs adjustment.

Advantages:

1. Hap's compliant.
2. Aerosol form, no extra equipment needed.
3. Feathers in invisibly for touch-up repairs.
4. Available in a wide variety of wood finishing shades.
5. Excellent transparency.

### Characteristics:

Weight per gallon: 6.38 lbs/gal \*(including propellant)

Solids % (wt): 8.84\*

Solids % (vol): 5.22\*

Package viscosity: 23-25 seconds, #1 Zahn cup\*

Dry time: Air dry @ 72 F, 35% relative humidity

To touch: 7 minutes

To handle: 15 minutes

To package: overnight

VOC's (coating): 5.53 lbs/gal (664.05 g/l)\*

VOC's (material): 4.13 lbs/gal (495.95 g/l)\*

VHAP's: 0.83 lbs VHAP's/lb solids \*

Package life: 3 years

\* = varies depending on color

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection – X

### Specifications:

Directions: Clean surface to be sprayed with Mohawk Wax Wash™ Remover. For best results, can temperature should be 65° - 90° F. SHAKE WELL BEFORE USING for at least one minute after ball rattles to ensure color uniformity. Point opening of spray button toward object, holding can 12 to 14 inches away from surface to be coated. Press spray button firmly. Use steady, even strokes. Several thin coats give better finish than one heavy coat. Allow coating to become tacky between coats. Clean spray button immediately by spraying with can upside down until no more product comes out. If clogged, remove spray button with a twisting motion and clean. Gently twist button onto can with opening turned away from you.

Note: Safety Cautions and Warnings based on M100-0007 and may vary based on color. Consult MSDS for individual product cautions and warnings.

### Safety Cautions:

Principal Hazards: DANGER! Extremely flammable liquid and vapor. Vapors may cause flash fire. Harmful or fatal if swallowed. Causes eye and skin irritation. May be harmful if absorbed through skin. Harmful if inhaled. Vapor harmful.

Other Hazards: Causes eye, skin, nose and throat irritation. Overexposure may cause Lung, Kidney damage. Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Harmful or fatal if swallowed. Cancer hazard: contains crystalline silica which can cause cancer. (Risk of cancer depends on duration and level of exposure.) Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. May be harmful if absorbed through skin.

Precautions: KEEP OUT OF REACH OF CHILDREN. Close container after each use. Wash thoroughly after handling. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Use only with adequate ventilation. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not get in eyes, in skin or clothing. Vapors may ignite explosively. Do not breathe dust, vapors or spray mist. Keep away from heat, sparks and flame.

First Aid: If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention immediately. Wash clothing before reuse. CLEAN contaminated shoes.

Handling: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

See Material Safety Data Sheet for complete information and First Aid

### **MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products  
Division of RPM Wood Finishes Group, Inc.  
P O Box 22000  
Hickory, NC 28603

Phone: 1-800-545-0047  
Fax: 1-800-721-1545