

# Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Tone Finish® Toner (13 oz. aerosols)

M101- color number (39 colors available)

**Product Description:** Mohawk Tone Finish® Toners are used throughout the industry for quick efficient professional touch-up. Tone Finish® Toners contain finely ground, non-fading pigments for color repairs that last. Toners adapt to various methods so as to blend in spot repairs. Adjustment of sheen is achieved with a topcoat of clear lacquers available in gloss, satin, flat and dead flat.

Advantages:

1. Hap's compliant.
2. Aerosol form, no extra equipment needed.
3. Feathers in invisibly for touch-up repairs.
4. Available in a wide variety of wood finishing shades.

### Characteristics:

Weight per gallon: 6.37 lbs/gal \*(including propellant)

Solids % (wt): 7.28\*

Solids % (vol): 4.63\*

Package viscosity: 23-25 seconds, #1 Zahn cup\*

Dry time: Air dry @ 72 F, 35% relative humidity

To touch: 7 minutes

To handle: 15 minutes

To package: overnight

VOC's (coating): 5.70 lbs/gal (684.27 g/l)\*

VOC's (material): 4.48 lbs/gal (538.22 g/l)\*

VHAP's: 0.75 lbs VHAP's/lb solids \*

Package life: 3 years

\* = varies depending on color

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection – X

### Specifications:

Directions: Clean surface to be sprayed with Mohawk Wax Wash™ Remover. For best results, can temperature should be 65 – 90 deg. F. SHAKE WELL BEFORE USING for at least one minute after ball rattles to ensure color uniformity. Point opening of spray button toward object, holding can 12 – 14 inches away from surface to be coated. Press spray button firmly. Use steady, even strokes. Several thin coats give a better finish than one heavy coat. Allow coating to become tacky between coats. Clean spray button immediately by spraying with can upside down until no more product comes out. If clogged, remove spray button with a twisting motion and clean. Gently twist button onto can with opening turned away from you.

### Safety Cautions:

Principal Hazards: DANGER! Extremely flammable liquid and vapor. Vapors may cause flash fire. Harmful or fatal if swallowed. Causes eye and skin irritation. Harmful if inhaled. Vapor harmful.

Contains: acetone, ethyl acetate, propane, n-butyl acetate, isobutane, toluene, isopropanol, isobutyl isobutyrate, crystalline silica

Precautions: Contents under pressure. Do not puncture, incinerate, or discard in a compactor. Do not store above 120° F, or in direct sunlight. Do not get in eyes, on skin or clothing. Do not breathe vapors. Use only with adequate ventilation. Keep away from heat, sparks and flame.

First Aid: If affected by product, remove to fresh air. If swallowed, do not induce vomiting. Flush eyes or skin immediately with plenty of water. If exposure occurs, get medical attention immediately.

KEEP OUT OF THE REACH OF CHILDREN.

For industrial and commercial use only.

See Material Safety Data Sheet for complete information and First Aid

**MSDS:** If Material Safety Data Sheet is required, contact:  
Mohawk Finishing Products  
Division of RPM Wood Finishes Group, Inc.  
P O Box 22000  
Hickory, NC 28603

Phone: 1-800-545-0047  
Fax: 1-800-721-1545