

# Mohawk

Finishing Products, Inc.

# Product Data Sheet

## Tone Finish Clears

M102-0420 (Gloss), 0422 (Satin), 0421 (Flat), 0485 (Dead Flat)

Available in 13 oz. Aerosol

**Product Description:** The Mohawk Tone Finish clears are the aerosol clears to compliment our Tone Finish Toners. These clears are formulated using the same fine ingredients that are used in our Tone Finishes. These products provide exceptional flow and protection on repairs. Given the choice of four different sheens repairs are made with excellent blend-in properties.

### Advantages:

1. Easy to use.
2. Blush resistant.
3. Excellent blend-in properties.
4. Good cold check resistance.
5. Excellent print and mar resistance.

### Product Limitations:

1. Designed for interior use only.

### **Characteristics:**

\*Weight per gallon (includes propellant): 6.26-6.56 lbs/gal

Flashpoint: <0 F/-17.8c

Package Viscosity: 23-25 seconds #1 Zahn cup

Dry Time: Air Dry @ 72 F, 35% relative humidity

To touch: 7 minutes

To handle: 15 minutes

To package: Overnight

Volatile Organic Compounds: Does not exceed 95% VOC

\*Specific Gravity (includes propellant): .680 - .780

Boiling Range: 1.0° - 300.0° F

\*Solids % by wt. (including propellant): 7.8 – 11.8%

Package Life: 3 years

60° Gloss Meter Readings:

Gloss 90+

Satin 45 – 50

Flat 15 – 20

Dead Flat 3 – 6

\*Hazardous Air Pollutants: 0.4 – 0.5 lbs / 1 lb solids

Air Quality Data: Non-Photochemically Reactive

\* Depending upon sheen

HMIS:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

**Specifications**

Directions: SHAKE WELL BEFORE USING. Surface should be clean, dry, finish sanded with wood moisture content of 6 – 8 % maximum. For best results, use only when can temperature is between 65 F and 90 F. Use steady even strokes while spraying, several thin coats give a better finish than one heavy coat. We recommend not more than 3 coats be applied in any 24 hour period. If sanding sealer is required, Mohawk Sanding Sealer (aerosol) M102-0423 is recommended. For packaging or rubbing, allow at least overnight drying.

Safety Cautions: Content are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

P O Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545