

Mohawk

Finishing Products, Inc.

Product Data Sheet

BLENDER FLOW-OUT TONER

M103-0419 (GLOSS), 0176 (FLAT)

AVAILABLE IN 13 OZ. AEROSOL

Product Description: Mohawk "Blender Flow-Out" is a high active solvent formula with excellent flow designed to blend in overspray and orange peel. This product is most suited as the final spot repair finish.

Advantages:

1. Easy to use.
2. Excellent blush resistance.
3. Removes overspray.
4. Blend in orange peel.

Product Limitations:

1. Designed for interior use only.

Characteristics:

Weight per gallon: 7.30 ± 0.1 lbs./gal.

Flashpoint: < 0 F/-17.8 c

Package Viscosity: 22-24 seconds #1 Zahn cup

Dry time: Air Dry @ 72 F, 35% relative humidity

To touch: 5 minutes

To handle: 10 minutes

To sand: 15 minutes

To recoat: 15 minutes

To package: overnight

Volatile Organic Compounds (VOC):

Not to exceed 815 grams/liter, 6.81 lbs./gal.

Spec. Gravity: 0.887 ± 0.01

Boiling Range: -30 F/-34 c

Non Volatile (wt): 7.50 ± 0.5%

Package Life: 3 years

Coverage: 80 square feet/gallon

60° Gloss Meter Readings:

Gloss: 85+

Flat: 15-20

HMIS:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

Hazardous Air Pollutants: 0.75 ± 0.05 lb./1 lb. solids

Air Quality Data: Non-Photochemically Reactive

Specifications:

Directions: SHAKE WELL BEFORE USING. Surface should be clean, dry, finish sanded with a wood moisture content of 6-8% maximum. For best results, use only when can temperature is between 65 °F and 90°F. Use steady even strokes while spraying. Several thin coats give a better finish than one heavy coat.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551