

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Finisher's Glaze™ Glazing Stain Aerosol

M114-Color number (13 oz. aerosols)

Available colors: M114-1435 Bt. Umber, 0224 Black, 1478 Van Dyke Brown, 0202 White, 0143 Raw Umber, 0384 Deep Mahogany, 0600 assortment

Product Description: Finisher's Glaze™ Glazing Stain (aerosol) is a medium viscosity glaze. Finisher's Glaze™ Glazing Stain is formulated to yield great workability, yet the solvent system is so coating compatible that you can topcoat within just minutes. The high pigment load assures the opacity you need for great coverage. Use this glaze for quick and easy touch-ups, finishing applications, refinishing, and expedient application on carvings and into corners. It may be used anywhere you would typically use a bulk glaze.

Advantages:

1. Truly professional glaze in an aerosol
2. Easy to use, no mess, no spills
3. 6 popular colors to choose from.
4. HAPS compliant

Characteristics:

Weight per gallon: 6.28 – 6.56 lbs/gal (including propellant)

Package viscosity: Medium body

Solids % (wt): 15.75 – 22.63

Solids % (vol): 9.58 – 12.34

Dry time: Air dry @ 72 F, 35% relative humidity

To topcoat: 5 minutes (mist coat to set glaze)

10 minutes (full wet coat for protection)

VOC's (coating): 5.06 - 5.28 lbs/gal (608.04 – 634.42 g/l)

VOC's (material): 5.06 – 5.28 lbs/gal (607.86 – 634.41 g/l)

VHAP's: 0.11 - 0.19 lbs VHAP's/lb solids

Package life: 3 years

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection – X

Specifications:

Directions: Shake can vigorously before use. Apply generously over a sealer or finish coat. Remove excess as needed with a soft cloth or brush to achieve the final desired effect of color. Allow to dry (approximately 20-35 minutes) before applying a topcoat. Use anywhere a bulk glaze can be used. Turn can upside down and clear nozzle for 5 seconds after use. Dispose of dirty rags immediately.

Safety Cautions: DANGER! Poison! Extremely flammable liquid and vapor. Vapors may cause flash fire. Contents under pressure. Harmful or fatal if swallowed. Causes eye and skin irritation. Harmful if inhaled. Vapor harmful. KEEP OUT OF REACH OF CHILDREN. For industrial and commercial use only.

Contents: aliphatic petroleum distillates, propane, alkyd resin solids, isobutane, methanol, 1,2,4-trimethylbenzene, aliphatic hydrocarbons, butanol, n-butyl acetate, m-xylene, ethylbenzene, benzene, toluene.

Precautions: Contents under pressure. Do not puncture, incinerate, or discard in a compactor. Do not get in eyes, on skin or clothing. Do not breathe vapors. Use only with adequate ventilation. Keep away from heat, sparks and flame.

First Aid: If affected by product, remove to fresh air. If swallowed, do not induce vomiting. Flush eyes or skin immediately with plenty of water. If exposure occurs, get medical attention immediately.

Warning: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

MSDS: If Material Safety Data Sheet is required, contact:
Mohawk Finishing Products
Division of RPM Wood Finishes Group, Inc.
P O Box 22000
Hickory, NC 28603

Phone: 1-800-545-0047
Fax: 1-800-721-1545