

# Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Wiping Wood Stain Aerosol

M145-Color number (13 oz. aerosols)

Available in 12 colors

**Product Description:** Mohawk Wiping Wood Stain Aerosol is a pigment wiping stain that will beautifully color wood and enhance the natural grain. It may be topcoated with any Mohawk clear finish. Wiping Wood Stains contain pigments that resist fading from UV rays.

Advantages:

1. Truly professional stain in an aerosol
2. Easy to use, no mess, no spills
3. Great for easy application on carved surfaces and hard to reach areas
4. 12 popular colors to choose from.
5. Colors are matches for corresponding Mohawk Wiping Wood Stains in bulk
6. HAPS compliant

### Characteristics:

Weight per gallon: 6.22 lbs/gal \* (including propellant)

Package viscosity: 23-25 seconds, Zahn #1\*

Solids % (wt): 10.50\*

Solids % (vol): 4.39\*

Dry time: Air dry @ 72 F, 35% relative humidity

To touch: 5 minutes

To handle: 10 minutes

To topcoat: 30 minutes

VOC's (coating): 5.56 lbs/gal (667.32 g/l)\*

VOC's (material): 5.56 lbs/gal (667.30 g/l)\*

VHAP's: 0.08 lbs VHAP's/lb solids\*

Package life: 3 years

\* values may vary slightly depending on color selected

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection – X

### Specifications:

**Directions:** Shake for one minute before application and regularly during long use. Apply stain generously. Spread evenly by wiping or brushing. Allow to flash off momentarily, and then use a clean absorbent cloth to remove excess. Dry (approximately 30 minutes) before sealing or topcoating. Clean nozzle by inverting the can and depressing the spray tip for 5 seconds.

**Safety Cautions:** DANGER! Extremely flammable liquid and vapor. Vapors may cause flash fire. Harmful or fatal if swallowed. Harmful if inhaled. Causes eye irritation. Vapor harmful

For industrial & commercial use only. KEEP OUT OF REACH OF CHILDREN.

Contents: aliphatic petroleum distillates, propane, aromatic hydrocarbons, isobutane, iron oxide red, 1,2,4 methylbenzene, aliphatic hydrocarbons, manganese oxide, naphthalene, carbon black, aromatic hydrocarbons, crystalline silica, ethylbenzene, benzene, toluene.

Precautions: Contents under pressure. Do not puncture, incinerate, or discard in a compactor. Do not store above 120° F, or in direct sunlight. Do not get in eyes, on skin or clothing. Do not breathe vapors. Use only with adequate ventilation. Keep away from heat, sparks and flame.

First Aid: If affected by product, remove to fresh air. If swallowed, do not induce vomiting. Flush eyes or skin immediately with plenty of water. If exposure occurs, get medical attention immediately.

Warning: This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm.

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products  
Division of RPM Wood Finishes Group, Inc.  
P O Box 22000  
Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545