

Mohawk

Finishing Products, Inc.

Product Data Sheet

Finish Remover No. 2™

M710-272

Available in 1 Gallon, 5 Gallons

Product Description: Mohawk Remover No. 2 is a non-flammable, semi-paste, quick-acting paint remover. Remover No. 2 has a viscosity (body) so that it will adhere to overhead or vertical surfaces. It is equally effective on wood m metal, plaster or masonry surfaces and on interior or exterior quality finishes. Remover No. 2 is effective on lacquers, varnishes, shellacs, catalyzed finishes, polyurethanes and other finishes. On some difficult to remove finishes, several applications of remover may be necessary. Remover No. 2 does not contain either acids or caustics that require subsequent neutralization before finishing can be done. Recommended for cleaning paintbrushes. Soak brush, then rinse clean with warm water.

Advantages

May be washed off with water.

Product Limitations:

Remover No. 2 is not effective on latex finishes.

Remover No. 2 is not effective in removal of dye colorants.

Remover No. 2 is poisonous and cannot be made non-poisonous.

Characteristics:

Weight per gallon: 8.80 ± 0.1 lbs/gal

Flashpoint: none observed

Package Viscosity: $4000\text{cps} \pm 500$, #3 @ 10 rpm

Volatile Organic Compounds (VOC): Not to exceed 1026 GPL, 8.6 lbs/gal

Specific Gravity: 1.056 ± 0.01

Boiling Range: 104 F/40 C

Coverage: 50-75 sq. ft./gal

Package Life: 3 years

Air Quality Data: Non-photochemically reactive

Hazardous Air Pollutants: 33.77 ± 0.5 lb./1 lb. Solids

HMIS

Health: 3

Flammability: 0

Reactivity: 0

Personal Protection: G

Specifications: Always use splash proof face shield, rubber gloves, neoprene apron and respirator with Remover No. 2. Remover No. 2 is ready for use as received in the can; no reduction of any kind is necessary.

Directions: Shake can well before using to insure homogeneous mixture. Flow on thick uniform coat from full brush, brushing only in one direction. Do not brush back and forth as when painting as this leaves holes in the film. Let remover do the work. Wait until test scraping indicates old paint is ready for removal. Remove with scraper, steel wool or with burlap. Wash the stripped surface with warm water and or M710-2007 Stripper Wash to remove residual wax before refinishing. Use brass bristle on open pored wood to remove wax residue.

Clean up with Mohawk Lacquer Reducer M650-010 or S-15 Reducer M650-250.

Safety Cautions: Contents are Non-Flammable. Keep away from heat m sparks and open flame. During use and until all vapors are gone, keep area well ventilated.
POISONOUS: Contains methanol. Cannot be made non-poisonous. May be harmful if absorbed through the skin. Contains Methylene Chloride, which has been shown to cause cancer in certain laboratory animal test. Risk to you health depends on the level and duration of exposure. Avoid breathing vapor and spray mist. **USE ONLY WITH ADEQUATE VENTILATION.** Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.
P O Box 22000
Hickory, NC 28602

Phone: 1-800-545-0047
Fax: 1-800-721-1545