Product Data Sheet

Finishing Products, Inc.

FISH EYE FLOWOUT LACQUER ADDITIVE M716-160 Available in 1 ounce and 8 ounce bottles

Product Description: Mohawk's "Fish Eye Flowout" helps prevent craters and fish-eyes in the lacquer surface. Caution needs to become paramount so as to not add more than the instructions permit.

Advantages:

- 1. Easy to use.
- 2. Quick results.
- 3. Convenient dropper bottle.

Product Limitations:

1. Do not over add. Some is "good" more is "better" does not apply.

Characteristics:

Weight per gallon: 7.67 \pm 0.1 lbs./gal. Flashpoint: 80° F/ 27 c

Spec. Gravity: 0.922 ± 0.01 Boiling Range: 281° F/ 138 c Non volatile (wt). $52.9 \pm 0.5\%$ Package Life: 3 years

Volatile Organic Compounds (VOC): Not To exceed 435 grams/liter, 3.65 lbs./gal.

Hazardous Air Pollutants: 0.9 lb. Max./1 lb. solids Air Quality Data: Photochemically Reactive

<u>HMIS:</u> Health: 1 Flammability: 3 Reactivity: 0 Personal Protection: B

Specifications:

Directions: Mix 10 drops per gallon, then add by drop until condition is eliminated. Avoid excess, Fisheye Flowout is not soluble in lower alcohols, such as shellacs. Observe precautions of finish to which Fisheye Flowout is added.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

<u>MSDS</u>: If Material Safety Data Sheet is required, contact: Mohawk Finishing Products, Inc. 4715 STHWY 30 Amsterdam, NY 12010-7417 Phone: 518-843-1380 Fax: 518-842-3551