# Safety Data Sheet



| 1. Identification                     |  |  |
|---------------------------------------|--|--|
| Product Information:<br>Product Name: | M734-0005<br>PATCHAL® PUTTY CORDOVAN 4 OZ  |  |
| Recommended Use:                      | Surface Preparation or Protection  |  |
| Supplied by:                          | Mohawk Finishing Products<br>Division of RPM Industrial Coatings Group<br>3194 B Hickory Blvd<br>Hudson, NC 28638<br>USA |  |
| Company Phone No:                     | (800) 522-8266   |  |
| Emergency Phone No. CHEMTREC:         | (800) 424-9300   |  |
| International Emergency No. CHEMTREC: | (703) 527-3887 (Collect calls are accepted)  |  |

# 2. Hazards Identification

GHS Classification Carc. 1B, Flam. Solid 1, Muta. 1B

Symbol(s) of Product



Signal Word Danger

#### Possible Hazards

2% of the mixture consists of ingredients of unknown acute toxicity

#### GHS HAZARD STATEMENTS

| Flammable Solid, category 1         | H228      | Flammable solid.  |
|-------------------------------------|-----------|---|
| Germ Cell Mutagenicity, category 1B | H340      | May cause genetic defects.  |
| Carcinogenicity, category 1B        | H350      | May cause cancer.   |
| GHS SDS PRECAUTIONARY STATEME       | INTS      |   |
|                                     | P210      | Keep away from heat No smoking.                                   |
|                                     | P240      | Ground/Bond container and receiving equipment.                    |
|                                     | P241      | Use explosion-proof electrical/ ventilating/ lighting/ equipment. |
|                                     | P280      | Wear eye protection/ face protection.                             |
|                                     | P405      | Store locked up.  |
|                                     | P201      | Obtain special instructions before use.                           |
|                                     | P308+P313 | IF exposed or concerned: Get medical advice/attention.            |

## 3. Composition/Information on ingredients

| Chemical Name                | CAS-No.    | <u>Wt. %</u> | GHS Symbols    | GHS Statements |
|------------------------------|------------|--------------|----------------|----------------|
| crystalline silica           | 14808-60-7 | 30-60        | No Information | No Information |
| petroleum distillate         | 64742-48-9 | 30-60        | GHS08          | H304-340-350   |
| modified complex hydrocarbon | 64742-60-5 | 5-10         | GHS07          | H332           |
| mixed glycercides            | 68308-54-3 | 1-5          | No Information | No Information |
| pariffin wax                 | 8002-74-2  | 1-5          | GHS07          | H332           |
| white petrolatum             | 8009-03-8  | 1-5          | GHS08          | H350           |
| iron oxide                   | 1309-37-1  | 1-5          | No Information | No Information |

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN: Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention.

FIRST AID - INGESTION: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

## 5. Fire-fighting Measures

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA flammable solid. Follow NFPA 400, Chapters 5 and 13 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipient fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

## 6. Accidental Release Measures

#### ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

## 7. Handling and Storage



HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or

drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

## 8. Exposure Controls/Personal Protection

| Ingredients with Occupational Exp<br>Chemical Name | osure Limits<br><u>ACGIH TLV-TWA</u> | ACGIH-TLV STEL | <u>OSHA PEL-TWA</u> | OSHA PEL-CEILING |
|--|--------------------------------------|----------------|---------------------|------------------|
| crystalline silica                                 | 0.025 mg/m3                          | N.D.           | 50 μg/m3            | N.D.             |
| petroleum distillate                               | N.D.                                 | N.D.           | N.D.                | N.D.             |
| modified complex hydrocarbon                       | N.D.                                 | N.D.           | N.D.                | N.D.             |
| mixed glycercides                                  | N.D.                                 | N.D.           | N.D.                | N.D.             |
| pariffin wax                                       | 2 mg/m3                              | N.D.           | N.D.                | N.D.             |
| white petrolatum                                   | N.D.                                 | N.D.           | N.D.                | N.D.             |
| iron oxide   | 5 mg/m3                              | N.D.           | 10 mg/m3            | N.D.             |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

#### Personal Protection



**RESPIRATORY PROTECTION:** In case of insufficient ventilation wear suitable respiratory equipment.

SKIN PROTECTION: Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



**EYE PROTECTION:** Safety glasses



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

N.I. = No Information

# 9. Physical and Chemical Properties

| Appearance:                    | Solid                     | Physical State:                             | Solid          |
|--------------------------------|---------------------------|---|----------------|
| Odor:                          | Oily Hydrocarbon          | Odor Threshold:                             | Not Determined |
| Density, g/cm3:                | 1.240                     | pH:   | Not Determined |
| Freeze Point, °F:              | Not Determined            | Viscosity:                                  | Not Determined |
| Solubility in Water:           | Not Determined            | Partition Coefficient, n-octanol/<br>water: | Not Determined |
| Decomposition temperature, °F: | Not Determined            | Explosive Limits, %:                        | Not Determined |
| Boiling Range, °F:             | Not determined            | Flash Point, °F:                            | 106 ° F        |
| Combustibility:                | Supports Combustion       | Auto-Ignition Temperature, °F:              | Not Determined |
| Evaporation Rate:              | Faster than Diethyl Ether | Vapor Pressure, mmHg:                       | Not determined |
| Vapor Density:                 | Not Determined            |   |                |

## 10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat, flames and sparks.

INCOMPATIBILITY: Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

## 11. Toxicological information

**\$**\*

Practical Experiences

EMERGENCY OVERVIEW: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: May cause cancer.

PRIMARY ROUTE(S) OF ENTRY:

#### Acute Toxicity Values The acute effects of this product have not been tested. Data on individual components are tabulated below

| CAS-No.    | Chemical Name        | Oral LD50       | Dermal LD50        | Vapor LC50   |
|------------|----------------------|-----------------|--------------------|--------------|
| 14808-60-7 | crystalline silica   | >5000 mg/kg     | >5000 mg/kg        | >20 mg/l Rat |
| 64742-48-9 | petroleum distillate | >5000 mg/kg Rat | >3160 mg/kg Rabbit | >20 mg/L Rat |

| 64742-60-5 | modified complex hydrocarbon |
|------------|------------------------------|
| 68308-54-3 | mixed glycercides            |
| 8002-74-2  | pariffin wax                 |
| 8009-03-8  | white petrolatum             |
| 1309-37-1  | iron oxide                   |

#### N.I. = No Information

## 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

>5000 mg/kg Rat

>3750 mg/kg Rat

>10000 mg/kg Rat

>5001

N.I.

>3600 mg/kg Rabbit >20

3600 mg/kg Rabbit

>5000 mg/kg Rat

>3600 mg/kg Rabbit >14 mg/l

>20.1

N.I.

>20 mg/l

>5001

## 13. Disposal Information



# Product

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

## 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

**DOT:** UN1263, PAINT, 3, II

IATA: UN1263, PAINT, 3, II

IMDG: UN1263, PAINT, 3, II

## 15. Regulatory Information

## **U.S. Federal Regulations:**

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Chronic Health Hazard

#### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

| Chemical Name | CAS-No.   |
|---------------|-----------|
| zinc          | 7440-66-6 |
| lead          | 7439-92-1 |

## **U.S. State Regulations:**

#### **CALIFORNIA PROPOSITION 65**

MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Crystalline Silica, Cancer, 43.4462% Lead, Reproductive Harm, 0%

### NOTICE

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in

| Revision Date:         | 7/27/2024   |   | Supersedes Date: 6/12 |   |                      |   |
|------------------------|---|---|-----------------------|---|----------------------|---|
| Reason for revision:   | 01 - Produ<br>03 - Comp<br>08 - Expos<br>09 - Physic<br>15 - Regul<br>Substance | Substance and/or Product Properties Changed in Section(s):<br>01 - Product Information<br>03 - Composition/Information on Ingredients<br>08 - Exposure Controls/Personal Protection<br>09 - Physical & Chemical Information<br>15 - Regulatory Information<br>Substance Hazardous Flag Changed<br>Revision Statement(s) Changed |                       |   |                      |   |
| Datasheet produced by: | Regulatory Department   |   |                       |   |                      |   |
| HMIS Ratings:          |   |   |                       |   |                      |   |
| Health: 2              | Flammability:   | 1   | Reactivity:           | 0 | Personal Protection: | Х |

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.