# Safety Data Sheet



1. Identification	
Product Information: Product Name: Recommended Use:	M102-0427 WATER CLEAR ACRYLIC SATIN Surface Preparation or Protection
Supplied by:	Mohawk Finishing Products Division of RPM Industrial Coatings Group 2220 US Hwy 70 SE Suite 100 Hickory, NC 28602 USA
Company Phone No:	(800) 522-8266
Emergency Phone No. CHEMTREC:	(800) 424-9300
International Emergency No. CHEMTREC:	(703) 527-3887 (Collect calls are accepted)

# 2. Hazards Identification

#### **GHS** Classification

Comp. Gas, Eye Irrit. 2A, FI Aer, 1, STOT RE 2, STOT SE 3 NE

#### Symbol(s) of Product



Signal Word Danger

#### Possible Hazards

7% of the mixture consists of ingredients of unknown acute toxicity

#### GHS HAZARD STATEMENTS

GIS HAZARD STATEMENTS		
Flammable Aerosol, category 1	H222	Extremely flammable aerosol.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Compressed Gas	H280	Contains gas under pressure; may explode if heated.
GHS SDS PRECAUTIONARY STATEM	ENTS	
	P210	Keep away from heat No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Pressurized container: Do not pierce or burn, even after use.
	P264	Wash face, hands and any exposed skin thoroughly after handling.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear eye protection/ face protection.
	P405	Store locked up.

P305+P351IF IN EYES: Rinse cautiously with water for several minutes. Remove contact<br/>lenses, if present and easy to do. Continue rinsing.P403+P233Store in a well-ventilated place. Keep container tightly closed.P410+P403Protect from sunlight. Store in a well-ventilated place.P410+P412Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.P260Do not breathe dust/fume/gas/mist/vapors/spray.P312Call a POISON CENTER or doctor if you feel unwell.P304+P340IF INHALED: Remove victim to fresh air and keep at rest in a position<br/>comfortable for breathing.

P337+P313 If eye irritation persists: Get medical advice/attention.

## 3. Composition/Information on ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
acetone	67-64-1	25-40	GHS02-GHS07	H225-302-319-332-336
isobutyl acetate	110-19-0	10-25	GHS02-GHS07	H225-332
propane	74-98-6	10-25	GHS02-GHS04	H220-280
n-butane	106-97-8	2.5-10	GHS02-GHS04	H220-280
m-xylene	108-38-3	2.5-10	GHS02-GHS07	H226-315-332
ethylbenzene	100-41-4	1.0-2.5	GHS02-GHS07-	H225-304-332-373
			GHS08	
o-xylene	95-47-6	1.0-2.5	GHS02-GHS07	H226-315-332
p-xylene	106-42-3	0.1-1.0	GHS02-GHS07	H226-315-332
n-butyl acetate	123-86-4	0.1-1.0	GHS02-GHS07	H226-336
cobalt octoate	136-52-7	<0.1	No Information	No Information

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN: Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/ attention.

FIRST AID - INGESTION: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

## 5. Fire-fighting Measures

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA Category 1 flammable aerosol. Follow NFPA 30B, Chapter 4 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipient fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire

# 6. Accidental Release Measures

#### ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

## 7. Handling and Storage



HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

## 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits <u>Chemical Name <u>ACGIH TLV-TWA</u><u>ACGIH-TLV STEL</u><u>OSHA PEL-TWA</u>OSHA PEL-CEILING</u>					
acetone	250 ppm	500 ppm	1000 ppm	N.D.	
isobutyl acetate	50 ppm	150 ppm	150 ppm	N.D.	
propane	N.D.	N.D.	1000 ppm	N.D.	
n-butane	N.D.	1000 ppm	N.D.	N.D.	
m-xylene	20 ppm	N.D.	100 ppm	N.D.	
ethylbenzene	20 ppm	N.D.	100 ppm	N.D.	
o-xylene	20 ppm	N.D.	N.D.	N.D.	
p-xylene	20 ppm	N.D.	100 ppm	N.D.	
n-butyl acetate	50 ppm	150 ppm	150 ppm	N.D.	
cobalt octoate	N.D.	N.D.	N.D.	N.D.	

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

#### Personal Protection



**RESPIRATORY PROTECTION:** Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.

SKIN PROTECTION: Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.

**EYE PROTECTION:** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



OTHER PROTECTIVE EQUIPMENT: No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

# 9. Physical and Chemical Properties

Appearance:	Cloudy Liquid	Physical State:	Aerosol
Odor:	Strong Solvent	Odor Threshold:	Not Determined
Density, g/cm3:	0.758	pH:	Not Determined
Freeze Point, °F:	Not Determined	Viscosity:	Not Determined
Solubility in Water:	Not Determined	Partition Coefficient, n-octanol/ water:	Not Determined
Decomposition temperature, °F:	Not Determined	Explosive Limits, %:	Not Determined
Boiling Range, °F:	Not Determined	Flash Point, °F:	-76 ° F
Combustibility:	Supports Combustion	Auto-Ignition Temperature, °F:	Not Determined
Evaporation Rate:	Faster than Diethyl Ether	Vapor Pressure, mmHg:	Not Determined
Vapor Density:	Not Determined		

N.I. = No Information

# 10. Stability and reactivity

STABILITY: Stable under normal conditions.
CONDITIONS TO AVOID: Heat, flames and sparks.
INCOMPATIBILITY: Acids, Bases, Oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

## 11. Toxicological information

Practical Experiences

**EMERGENCY OVERVIEW:** No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: No Information

#### PRIMARY ROUTE(S) OF ENTRY:

Eye Contact, Inhalation

## Acute Toxicity Values

## The acute effects of this product have not been tested. Data on individual components are tabulated below

100-41-4         ethylbenzene         3500 mg/kg Rat         15400 mg/kg Rabbit         17.2 mg/L Rat           95-47-6         o-xylene         3608 mg/kg Rat         14100 mg/kg Rabbit         >20 mg/l Rat           106-42-3         p-xylene         4029 mg/kg Rat         >2000 mg/kg rabbit         >20 mg/l Rat           123-86-4         n-butyl acetate         14130 mg/kg Rat         >17600 mg/kg Rabbit         23.4 mg/l Rat	CAS-No. 67-64-1 110-19-0 74-98-6 108-38-3	<u>Chemical Name</u> acetone isobutyl acetate propane m-xylene	<u>Oral LD50</u> 1800 mg/kg Rat 15400 mg/kg Rat N.I. 5000 mg/kg Rat	Dermal LD50 20000 mg/kg Rabbit >17400 mg/kg Rabbit N.I. 6500 mg/kg Rabbit	658 mg/L Rat >20 mg/l Rat
136-52-7 cobalt octoate 3129 mg/kg Rat >5000 mg/kg Rabbit N.I.	95-47-6 106-42-3	o-xylene p-xylene	3608 mg/kg Rat 4029 mg/kg Rat	14100 mg/kg Rabbit >2000 mg/kg rabbit >17600 mg/kg Rabbit	>20 mg/l Rat >20 mg/l Rat 23.4 mg/l Rat

N.I. = No Information

## 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

## 13. Disposal Information



Product

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

## 14. Transport Information

#### SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT: LIMITED QUANTITY

IATA: ID8000, CONSUMER COMMODITY, 9

IMDG: LIMITED QUANTITY UN1950

# 15. Regulatory Information

## **U.S. Federal Regulations:**

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.	<u>Wt. %</u>
m-xylene	108-38-3	3.25
ethylbenzene	100-41-4	2.47
o-xylene	95-47-6	1.34

#### TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name	<u>CAS-No.</u>
octamethylcyclotetrasiloxane	556-67-2

## U.S. State Regulations:

#### **CALIFORNIA PROPOSITION 65**

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Ethylbenzene, Cancer, 2.4704% Toluene, Reproductive Harm, 0.0838%

## 16. Other Information


Revision D	ate:	8/22/2024		Su	persedes D	ate:	7/26/2024
Reason for revision:Product Composition Changed Substance and/or Product Properties Changed i 09 - Physical & Chemical Information		ged in Sectio	on(s):				
Datasheet	produced by:	Regulatory	Department				
HMIS Rat	ings:						
Health:	2	Flammability:	4	Reactivity:	0	Personal Protection:	Х
-							

Volatile Organic Compounds, gr/ltr: 566

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapor.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.

H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H336	May cause drowsiness or dizziness.		
H373	May cause damage to organs through prolonged or repeated exposure.		
Icons for GHS Pictograms shown in Section 3 describing each ingredient:			



The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.