# Safety Data Sheet



| 1. Identification   |   |
|---|---|
| Product Information:<br>Product Name:<br>Recommended Use: | M293-0005<br>BACKGROUND MARKER GLAZE HANG-UP TOASTED ALMOND<br>Surface Preparation or Protection                                  |
| Supplied by:  | Mohawk Finishing Products<br>Division of RPM Industrial Coatings Group<br>2220 US Hwy 70 SE Suite 100<br>Hickory, NC 28602<br>USA |
| Company Phone No:   | (800) 522-8266  |
| Emergency Phone No. CHEMTREC:                             | (800) 424-9300  |
| International Emergency No. CHEMTREC:                     | (703) 527-3887 (Collect calls are accepted)   |

## 2. Hazards Identification

| GHS   | Cla | assific | atior | า |
|-------|-----|---------|-------|---|
| Carc. | 2,  | Flam.   | Liq.  | 2 |

Symbol(s) of Product



Signal Word Danger

### GHS HAZARD STATEMENTS

| Flammable Liquid, category 2 | H225 | Highly flammable liquid and vapour. |
|------------------------------|------|-------------------------------------|
| Carcinogenicity, category 2  | H351 | Suspected of causing cancer.        |

| EMENTS<br>Store in a well-ventilated place. Keep cool.   |
|--|
| ENTS   |
| Keep away from heat No smoking.  |
| Keep container tightly closed.   |
| Ground/Bond container and receiving equipment.   |
| Use explosion-proof electrical/ ventilating/ lighting/ equipment.  |
| Use only non-sparking tools.   |
| Take precautionary measures against static discharge.  |
| Wear eye protection/ face protection.  |
| Store locked up.   |
| IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
|  |

#### P201 P308+P313

Obtain special instructions before use. IF exposed or concerned: Get medical advice/attention.

### 3. Composition/Information on ingredients

| <u>Chemical Name</u><br>ethanol<br>n-butyl acetate<br>titanium dioxide<br>pm acetate       | <u>CAS-No.</u><br>64-17-5<br>123-86-4<br>13463-67-7<br>108-65-6<br>67-63-0 | <u>Wt. %</u><br>40-55<br>10-25<br>2.5-10<br>1.0-2.5 | GHS Symbols<br>GHS02<br>GHS02-GHS07<br>GHS08<br>GHS02-GHS07           | GHS Statements<br>H225<br>H226-336<br>H351<br>H226-332<br>H226-332 |
|--|--|---|---|--|
| isopropanol<br>aliphatic petroleum distillates<br>crystalline silica<br>ethylbenzene       | 67-63-0<br>64742-47-8<br>14808-60-7<br>100-41-4                            | 1.0-2.5<br>1.0-2.5<br>0.1-1.0<br>0.1-1.0            | GHS02-GHS07<br>GHS07-GHS08<br>No Information<br>GHS02-GHS07-<br>GHS08 | H225-302-319-336<br>H304-332<br>No Information<br>H225-304-332-373 |
| polyoxyethylene dinonyphenyl ether phosphate<br>surfactant<br>alkyl phenol phosphate ester | 39464-64-7<br>68891-21-4<br>68412-53-3                                     | <0.1<br><0.1<br><0.1                                | No Information<br>No Information<br>No Information                    | No Information<br>No Information<br>No Information                 |

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/ shower.

FIRST AID - INGESTION: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

### 5. Fire-fighting Measures

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

### 6. Accidental Release Measures

#### ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred,

and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

### 7. Handling and Storage



HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

### 8. Exposure Controls/Personal Protection

| Ingredients with Occupational Exposure Limits   |               |                |                     |                  |  |  |
|---|---------------|----------------|---------------------|------------------|--|--|
| Chemical Name                                   | ACGIH TLV-TWA | ACGIH-TLV STEL | <u>OSHA PEL-TWA</u> | OSHA PEL-CEILING |  |  |
| ethanol   | N.D.          | 1000 ppm       | 1000 ppm            | N.D.             |  |  |
| n-butyl acetate                                 | 50 ppm        | 150 ppm        | 150 ppm             | N.D.             |  |  |
| titanium dioxide                                | 0.2 mg/m3     | N.D.           | 15 mg/m3            | N.D.             |  |  |
| pm acetate                                      | N.D.          | N.D.           | N.D.                | N.D.             |  |  |
| isopropanol                                     | 200 ppm       | 400 ppm        | 400 ppm             | N.D.             |  |  |
| aliphatic petroleum distillates                 | N.D.          | N.D.           | N.D.                | N.D.             |  |  |
| crystalline silica                              | 0.025 mg/m3   | N.D.           | 50 µg/m3            | N.D.             |  |  |
| ethylbenzene                                    | 20 ppm        | N.D.           | 100 ppm             | N.D.             |  |  |
| polyoxyethylene dinonyphenyl ether<br>phosphate | N.D.          | N.D.           | N.D.                | N.D.             |  |  |
| surfactant                                      | N.D.          | N.D.           | N.D.                | N.D.             |  |  |
| alkyl phenol phosphate ester                    | N.D.          | N.D.           | N.D.                | N.D.             |  |  |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

#### **Personal Protection**

**RESPIRATORY PROTECTION:** Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.

SKIN PROTECTION: Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



**EYE PROTECTION:** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



OTHER PROTECTIVE EQUIPMENT: No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

### 9. Physical and Chemical Properties

| Appearance:                         | Colored Liquid                              | Physical State:                             | Liquid         |
|-------------------------------------|---|---|----------------|
| Odor:                               | Moderately Strong Alcohol                   | Odor Threshold:                             | Not Determined |
| Density, g/cm3:                     | 0.982                                       | pH:   | Not Determined |
| Freeze Point, °F:                   | Not Determined                              | Viscosity:                                  | Not Determined |
| Solubility in Water:                | Not Determined                              | Partition Coefficient, n-octanol/<br>water: | Not Determined |
| Decomposition temperature, °F:      | Not Determined                              | Explosive Limits, %:                        | Not Determined |
| Boiling Range, °F:                  | > 100 °F                                    | Flash Point, °F:                            | 55 ° F         |
| Combustibility:                     | Supports Combustion                         | Auto-Ignition Temperature, °F:              | Not Determined |
| Evaporation Rate:<br>Vapor Density: | Faster than Diethyl Ether<br>Not Determined | Vapor Pressure, mmHg:                       | Not Determined |

N.I. = No Information

### 10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat, flames and sparks.

INCOMPATIBILITY: Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

### 11. Toxicological information



Practical Experiences

EMERGENCY OVERVIEW: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: May cause cancer.

This product contains Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

#### PRIMARY ROUTE(S) OF ENTRY:

Skin Contact

#### Acute Toxicity Values The acute effects of this product have not been tested. Data on individual components are tabulated below

| 123-86-4 n-butyl acetate 14130 mg/kg Rat >17600 mg/kg Rabb   13463-67-7 titanium dioxide >10000 mg/kg Rat >10000 mg/kg Rabb   108-65-6 pm acetate 8532 mg/kg Rat >5000 mg/kg Rabbit   67-63-0 isopropanol 1870 mg/kg Rat 4059 mg/kg Rabbit   64742-47-8 aliphatic petroleum distillates >5000 mg/kg Rat >2000 mg/kg Rabbit   14808-60-7 crystalline silica >5000 mg/kg Rat >5000 mg/kg   100-41-4 ethylbenzene 3500 mg/kg Rat 15400 mg/kg Rabbit | it >20 mg/L<br>72.6 mg/L Rat<br>it >13 mg/L Rat<br>>20 mg/l Rat |
|--|---|
|--|---|

#### N.I. = No Information

### 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

### 13. Disposal Information



Product

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

### 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

**DOT:** LIMITED QUANTITY

IATA: ID8000, CONSUMER COMMODITY, 9

IMDG: LIMITED QUANTITY UN1263

### 15. Regulatory Information

### **U.S. Federal Regulations:**

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Chronic Health Hazard

#### SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

| Chemical Name | CAS-No.   |
|---------------|-----------|
| lead          | 7439-92-1 |
| mercury       | 7439-97-6 |

### U.S. State Regulations:

#### **CALIFORNIA PROPOSITION 65**

MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Titanium Dioxide, Cancer, 8.2322% Toluene, Reproductive Harm, 0.0141%

#### NOTICE

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in

### 16. Other Information

| Revision Date:         | 8/26/2024            |    | Supersedes Da | te: | 7/27/2024 |
|------------------------|----------------------|----|---------------|-----|-----------|
| Reason for revision:   | No Information       |    |               |     |           |
| Datasheet produced by: | Regulatory Departmer | it |               |     |           |
| HMIS Ratings:          |                      |    |               |     |           |

|  | Health: | 2 | Flammability: | 3 | Reactivity: | 0 | Personal Protection: | X |
|--|---------|---|---------------|---|-------------|---|----------------------|---|
|--|---------|---|---------------|---|-------------|---|----------------------|---|

Volatile Organic Compounds, gr/ltr:

612

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

| H225 | Highly flammable liquid and vapour.                                |
|------|--|
| H226 | Flammable liquid and vapor.  |
| H302 | Harmful if swallowed.  |
| H304 | May be fatal if swallowed and enters airways.                      |
| H319 | Causes serious eye irritation.                                     |
| H332 | Harmful if inhaled.  |
| H336 | May cause drowsiness or dizziness.                                 |
| H351 | Suspected of causing cancer.                                       |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

#### Icons for GHS Pictograms shown in Section 3 describing each ingredient:



The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.