Safety Data Sheet



1. Identification

Product Information: M294-0158

Product Name: BACKGROUND MARKER TOUCH-UP CRANBERRY

Recommended Use: Surface Preparation or Protection

Mohawk Finishing Products Supplied by:

Division of RPM Wood Finishes Group, Inc.

2220 US Hwy 70 SE Suite 100

Hickory, NC 28602

(800) 424-9300

USA

Company Phone No: (800) 522-8266 **Emergency Phone No. CHEMTREC:**

International Emergency No. CHEMTREC: (703) 527-3887 (Collect calls are accepted)

2. Hazards Identification

GHS Classification

Asp. Tox. 1, Carc. 1B, Flam. Liq. 2, Skin Irrit. 2, STOT RE 2, STOT SE 3 NE

Symbol(s) of Product







Signal Word Danger

GHS HAZARD STATEMENTS

H225 Flammable Liquid, category 2 Highly flammable liquid and vapour.

Skin Irritation, category 2 H315 Causes skin irritation.

STOT, single exposure, category 3, NE H336 May cause drowsiness or dizziness.

Carcinogenicity, category 1B H350 May cause cancer.

STOT, repeated exposure, category 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard, category 1 H304 May be fatal if swallowed and enters airways.

GHS LABEL PRECAUTIONARY STATEMENTS

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No P210

smoking.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P331 Do NOT induce vomiting.

P405 Store locked up.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P362+P364 Take off contaminated clothing and wash it before reuse.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P332+P313 If skin irritation occurs: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

GHS SDS PRECAUTIONARY STATEMENTS

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

3. Composition/Information on ingredients

Chemical Name	<u>CAS-No.</u>	<u>Wt. %</u>	GHS Symbols	GHS Statements
ethanol	64-17-5	40-55	GHS02	H225
toluene	108-88-3	25-40	GHS02-GHS07- GHS08	H225-304-315-332-336-373
isopropanol petroleum distillate	67-63-0 64742-54-7	2.5-10 0.1-1.0	GHS02-GHS07 GHS08	H225-302-319-336 H350

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

FIRST AID - INGESTION: Do NOT induce vomiting. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

FIREFIGHTING EQUIPMENT: This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

US GHS SDS (English)

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

7. Handling and Storage





HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING	
ethanol	N.D.	1000 ppm	1000 ppm	N.D.	
toluene	20 ppm	N.D.	200 ppm	300 ppm	
isopropanol	200 ppm	400 ppm	400 ppm	N.D.	
petroleum distillate	N.D.	N.D.	N.D.	N.D.	

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

Personal Protection



RESPIRATORY PROTECTION: Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.



SKIN PROTECTION: Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



EYE PROTECTION: Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



OTHER PROTECTIVE EQUIPMENT: No Information



HYGIENIC PRACTICES: It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

9. Physical and Chemical Properties

Appearance: Colored Liquid Physical State: LIQUID

Odor: Moderately Strong Alcohol Odor Threshold: Not determined

Density, g/cm3: 0.859 pH: Not determined

Freeze Point, °F: Not determined Viscosity: Not determined

Solubility in Water:

Not determined

Partition Coefficient, n-octanol/
water:

Not determined

Decomposition temperature, °F: Not determined Explosive Limits, %: Not determined

Boiling Range, °F: > 100 °F Flash Point, °F: 39 ° F

Combustibility:Supports CombustionAuto-Ignition Temperature, °F:Not determinedEvaporation Rate:Faster than Diethyl EtherVapor Pressure, mmHg:Not determined

Vapor Density: Not determined

N.I. = No Information

10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat, flames and sparks. **INCOMPATIBILITY:** Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

11. Toxicological information



Practical Experiences

EMERGENCY OVERVIEW: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information
EFFECT OF OVEREXPOSURE - INGESTION: No Information
EFFECT OF OVEREXPOSURE - INHALATION: No Information
EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: May cause cancer.

PRIMARY ROUTE(S) OF ENTRY:

Skin Contact, Ingestion, Inhalation

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

 CAS-No.
 Chemical Name
 Oral LD50
 Dermal LD50
 Vapor LC50

 64-17-5
 ethanol
 7060 mg/kg Rat
 15,800 mg/kg
 124.7 mg/L Rat

 108-88-3
 toluene
 2600 mg/kg Rat
 12000 mg/kg Rabbit
 12.5 mg/L Rat

 67-63-0
 isopropanol
 1870 mg/kg Rat
 4059 mg/kg Rabbit
 72.6 mg/L Rat

64742-54-7 petroleum distillate >15000 mg/kg Rat >5000 mg/kg Rabbit N.I.

N.I. = No Information

12. Ecological information

ECOLOGICAL INFORMATION: Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

13. Disposal Information



Product

DISPOSAL METHOD: Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT: CONSUMER COMMODITY

IATA: ID8000, CONSUMER COMMODITY, 9

IMDG: LIMITED QUANTITY UN1263

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

 Chemical Name
 CAS-No.
 Wt. %

 toluene
 108-88-3
 27.68

TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CAS-No. **Chemical Name** octamethylcyclotetrasiloxane 556-67-2

U.S. State Regulations:

CALIFORNIA PROPOSITION 65

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Ethylbenzene, Cancer, 0.0841% Toluene, Reproductive Harm, 27.6752%

16. Other Information

3/11/2021 Supersedes Date: **Revision Date:** 7/27/2021

Reason for revision: Substance and/or Product Properties Changed in Section(s):

08 - Exposure Controls/Personal Protection 09 - Physical & Chemical Information 11 - Toxicological Information

15 - Regulatory Information 16 - Other Information

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	2	Flammability:	3	Reactivity:	0	Personal Protection:	X
---------	---	---------------	---	-------------	---	----------------------	---

Volatile Organic Compounds, gr/ltr: 734

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

Highly flammable liquid and vapour. H225

H302 Harmful if swallowed.

May be fatal if swallowed and enters airways. H304

H315 Causes skin irritation. H319 Causes serious eye irritation.

Harmful if inhaled. H332

H336 May cause drowsiness or dizziness.

H350 May cause cancer.

May cause damage to organs through prolonged or repeated exposure. H373

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02 GHS07 GHS08

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.