Safety Data Sheet

1. Identification

Product Information: M545-4084

Product Name: 8XWIPING WOOD™ STAIN CHERRY 8 OZ

Recommended Use: Surface Preparation or Protection

Supplied by:
Mohawk Finishing Products
Division of RPM Wood Finishes Group, Inc.
2220 US Hwy 70 SE Suite 100
Hickory, NC 28602
USA

Company Phone No: (800) 522-8266

Emergency Phone No. CHEMTREC: (800) 424-9300

International Emergency No. CHEMTREC: (703) 527-3887 (Collect calls are accepted)

2. Hazards Identification

GHS Classification
Acute Tox. 3 Inhalation, Carc. 1B, Eye Irrit. 2, Flam. Liq. 3, Muta. 1B, Skin Irrit. 2, STOT RE 1, STOT SE 3 RTI

Symbol(s) of Product

Signal Word
Danger

Possible Hazards
1% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Germ Cell Mutagenicity, category 1B	H340	May cause genetic defects.
Carcinogenicity, category 1B	H350	May cause cancer.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Acute Toxicity, Inhalation, category 3	H331	Toxic if inhaled.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2	H319	Causes serious eye irritation.

GHS LABEL PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P403+P235	Store in a well-ventilated place. Keep cool.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P202	Do not handle until all safety precautions have been read and understood.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P271	Use only outdoors or in a well-ventilated area.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P311	Call a POISON CENTER or doctor/physician.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P270	Do not eat, drink or smoke when using this product.

3. Composition/Information on ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
aromatic hydrocarbons	64742-95-6	40-55	GHS06-GHS08	H304-331-340-350
1,2,4-trimethylbenzene	95-63-6	10-25	GHS02-GHS07	H226-315-319-332-335
aromatic hydrocarbons	64742-94-5	2.5-10	GHS06-GHS08	H304-312-330
aliphatic petroleum distillates	64742-88-7	1.0-2.5	GHS07-GHS08	H304-332-372
magnesium silicate hydrate	14807-96-6	1.0-2.5	GHS07	H302-312
naphthalene	91-20-3	1.0-2.5	GHS06-GHS08	H302-312-330-351
barium sulfate	7727-43-7	0.1-1.0	No Information	No Information
cumene	98-82-8	0.1-1.0	GHS02-GHS07-GHS08	H226-302-304-332-335
aliphatic petroleum distillates	64742-47-8	0.1-1.0	GHS07-GHS08	H304-332
n-butyl acetate	123-86-4	0.1-1.0	GHS02-GHS07	H226-336
crystalline silica	14808-60-7	0.1-1.0	GHS07	H302
carbon black	1333-86-4	0.1-1.0	GHS02	H251
ethanol	64-17-5	0.1-1.0	GHS02	H225

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

FIRST AID - INGESTION: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

FIREFIGHTING EQUIPMENT: This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

7. Handling and Storage

HANDLING: Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
aromatic hydrocarbons	N.D.	N.D.	N.D.	N.D.
1,2,4-trimethylbenzene	N.D.	N.D.	N.D.	N.D.

aromatic hydrocarbons	N.D.	N.D.	N.D.	N.D.
aliphatic petroleum distillates	N.D.	N.D.	N.D.	N.D.
magnesium silicate hydrate	2 mg/m3	N.D.	N.D.	N.D.
naphthalene	10 ppm	N.D.	10 ppm	N.D.
barium sulfate	5 mg/m3	N.D.	15 mg/m3	N.D.
cumene	50 ppm	N.D.	50 ppm	N.D.
aliphatic petroleum distillates	N.D.	N.D.	N.D.	N.D.
n-butyl acetate	50 ppm	150 ppm	150 ppm	N.D.
crystalline silica	0.025 mg/m3	N.D.	50 µg/m3	N.D.
carbon black	3 mg/m3	N.D.	3.5 mg/m3	N.D.
ethanol	N.D.	1000 ppm	1000 ppm	N.D.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

Personal Protection

RESPIRATORY PROTECTION: Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.

SKIN PROTECTION: Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.

EYE PROTECTION: Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.

OTHER PROTECTIVE EQUIPMENT: No Information

HYGIENIC PRACTICES: It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

9. Physical and Chemical Properties

Appearance:	Colored Liquid	**Physical State:**	LIQUID
Odor:	Oily Hydrocarbon	**Odor Threshold:**	Not determined
Density, g/cm3:	0.952	**pH:**	Not determined
Freeze Point, °F:	Not determined	**Viscosity:**	Not determined
Solubility in Water:	Not determined	**Partition Coefficient, n-octanol/ water:**	Not determined
Decomposition temperature, °F:	Not determined	**Explosive Limits, %:**	Not determined
Boiling Range, °F:	> 100 °F	**Flash Point, °F:**	108 ° F
Combustibility:	Supports Combustion	**Auto-Ignition Temperature, °F:**	Not determined
Evaporation Rate:	Faster than Diethyl Ether	**Vapor Pressure, mmHg:**	Not determined
Vapor Density:	Not determined		

N.I. = No Information

10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Heat, flames and sparks.

INCOMPATIBILITY: Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

11. Toxicological information

Practical Experiences

EMERGENCY OVERVIEW: No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information

EFFECT OF OVEREXPOSURE - INGESTION: No Information

EFFECT OF OVEREXPOSURE - INHALATION: No Information

EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

CARCINOGENICITY: May cause cancer.

PRIMARY ROUTE(S) OF ENTRY:

Eye Contact, Skin Contact, Inhalation

Acute Toxicity Values
The acute effects of this product have not been tested. Data on individual components are tabulated below

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
64742-95-6	aromatic hydrocarbons	14000 mg/kg Rat	>2000 mg/kg Rabbit	>4.96 mg/l Rat

95-63-6	1,2,4-trimethylbenzene	3280 mg/kg Rat	>3160 mg/kg Rabbit	18 mg/L Rat
64742-94-5	aromatic hydrocarbons	>5000 mg/kg Rat	>1744 mg/kg Rabbit	>0.6 mg/L Rat
64742-88-7	aliphatic petroleum distillates	>5000 mg/kg Rat	>3000 mg/kg Rabbit	>13 mg/L Rat
14807-96-6	magnesium silicate hydrate	>1600 mg/kg Rat	>1600 mg/kg Rat	N.I.
91-20-3	naphthalene	1110 mg/kg Rat	1120 mg/kg Rabbit	>.3 mg/L Rat
7727-43-7	barium sulfate	307000 mg/kg Rat	N.I.	N.I.
98-82-8	cumene	1400 mg/kg Rat	10603 mg/kg Rabbit	>20 mg/l
64742-47-8	aliphatic petroleum distillates	>5000 mg/kg Rat	>2000 mg/kg Rabbit	>13 mg/L Rat
123-86-4	n-butyl acetate	14130 mg/kg Rat	>17600 mg/kg Rabbit	23.4 mg/l Rat
14808-60-7	crystalline silica	500 mg/kg Rat	N.I.	>20 mg/l Rat
1333-86-4	carbon black	>5000 mg/kg Rat	>3000 mg/kg Rabbit	>20 mg/l
64-17-5	ethanol	7060 mg/kg Rat	15,800 mg/kg	124.7 mg/L Rat

N.I. = No Information

12. Ecological information

ECOLOGICAL INFORMATION: Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

13. Disposal Information

Product

DISPOSAL METHOD: Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT:	CONSUMER COMMODITY
IATA:	ID8000, CONSUMER COMMODITY, 9
IMDG:	LIMITED QUANTITY UN1263

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Chronic Health Hazard, Acute Health Hazard

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.
1,2,4-trimethylbenzene	95-63-6
naphthalene	91-20-3

TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical Name	CAS-No.
mercury	7439-97-6

U.S. State Regulations:

CALIFORNIA PROPOSITION 65

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Naphthalene, Cancer, 1.0084%
Toluene, Reproductive Harm, 0.0002%

16. Other Information

Revision Date: 2/17/2019 **Supersedes Date:** 9/7/2018

Reason for revision: Substance and/or Product Properties Changed in Section(s):
02 - Hazards Identification
03 - Composition/Information on Ingredients
11 - Toxicological Information
Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	2	**Flammability:**	2	**Reactivity:**	0	**Personal Protection:**	X

Volatile Organic Compounds, gr/ltr: 807

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H251	Self-heating: may catch fire.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS02

GHS06

GHS07

GHS08

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.