# Safety Data Sheet



### 1. Identification

Product Information: M850-20915

Product Name: E-Z FLOW LEATHER MARKER BURGUNDY 47707

Recommended Use: Surface Preparation or Protection

Supplied by: Mohawk Finishing Products

Division of RPM Industrial Coatings Group

2220 US Hwy 70 SE Suite 100

Hickory, NC 28602

USA

Company Phone No: (800) 522-8266

Emergency Phone No. CHEMTREC: (800) 424-9300

International Emergency No. CHEMTREC: (703) 527-3887 (Collect calls are accepted)

### 2. Hazards Identification

### **GHS Classification**

Flam. Liq. 2, Skin Sens. 1

#### Symbol(s) of Product





Signal Word

Danger

#### **GHS HAZARD STATEMENTS**

Flammable Liquid, category 2 H225 Highly flammable liquid and vapour. Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P235 Store in a well-ventilated place. Keep cool.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P210 Keep away from heat. - No smoking.
P233 Keep container tightly closed.

P240 Ground/Bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

### 3. Composition/Information on ingredients

<u>Chemical Name</u>	CAS-No.	Wt. %	GHS Symbols	GHS Statements
isopropanol	67-63-0	2.5-10	GHS02-GHS07	H225-302-319-336
dipropylene glycol monomethyl ether	34590-94-8	2.5-10	No Information	No Information
triethylamine	121-44-8	0.1-1.0	GHS02-GHS05-	H225-302-311-314-331-335
			GHS06-GHS07	
octadec-9-enoic acid	1095-66-5	0.1-1.0	No Information	No Information
carbon black	1333-86-4	0.1-1.0	GHS02	H251
polyethylene glycol octadecyl ether	9005-00-9	<0.1	GHS07	H302
ethoxylated isoalcohols c-13 rich	78330-21-9	<0.1	No Information	No Information
modified complex hydrocarbon	64742-60-5	<0.1	GHS07	H332

The exact percentage (concentration) of ingredients is being withheld as a trade secret.

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

### 4. First-aid Measures



FIRST AID - EYE CONTACT: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

FIRST AID - SKIN CONTACT: IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

FIRST AID - INGESTION: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

FIRST AID - INHALATION: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

## 5. Fire-fighting Measures

SPECIAL FIREFIGHTING PROCEDURES: Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

**FIREFIGHTING EQUIPMENT:** This is a NFPA/OSHA Class 1B or less flammable liquid. Follow NFPA30, Chapter 16 for fire protection and fire suppression. Use a dry chemical, carbon dioxide, or similar ABC fire extinguisher for incipeint fires. Water may be used to cool and prevent rupture of containers that are exposed to heat from fire.

### Accidental Release Measures

**ENVIRONMENTAL MEASURES:** No Information

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred,

and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

### 7. Handling and Storage





**HANDLING:** Avoid inhalation and contact with eyes, skin, and clothing. Wash hands thoroughly after handling and before eating or drinking. In keeping with safe handling practices, avoid ignition sources (smoking, flames, pilot lights, electrical sparks); ground and bond containers when transferring the material to prevent static electricity sparks that could ignite vapor and use spark proof tools and explosion proof equipment. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury.

STORAGE: Keep containers closed when not in use. Store in cool well ventilated space away from incompatible materials.

### 8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
isopropanol	200 ppm	400 ppm	400 ppm	N.D.
dipropylene glycol monomethyl ether	50 ppm	N.D.	100 ppm	N.D.
triethylamine	0.5 ppm	1 ppm	25 ppm	N.D.
octadec-9-enoic acid	N.D.	N.D.	N.D.	N.D.
carbon black	3 mg/m3	N.D.	3.5 mg/m3	N.D.
polyethylene glycol octadecyl ether	N.D.	N.D.	N.D.	N.D.
ethoxylated isoalcohols c-13 rich	N.D.	N.D.	N.D.	N.D.
modified complex hydrocarbon	N.D.	N.D.	N.D.	N.D.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established N.D. = Not Determined

#### **Personal Protection**



**RESPIRATORY PROTECTION:** Use adequate engineering controls and ventilation to keep levels below recommended or statutory exposure limits. If exposure levels exceed limits use appropriate approved respiratory protection equipment.



**SKIN PROTECTION:** Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.



**EYE PROTECTION:** Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.



**OTHER PROTECTIVE EQUIPMENT:** No Information



**HYGIENIC PRACTICES:** It is good practice to avoid contact with the product and/or its vapors, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

### 9. Physical and Chemical Properties

Appearance: Colored Liquid Physical State: Liquid

Odor: None to Very Faint Odor Threshold: Not Determined

**Density, g/cm3:** 1.004 **pH**: 8.3

Freeze Point, °F: Not Determined Viscosity: Not Determined

Solubility in Water:

Not Determined

Partition Coefficient, n-octanol/
water:

Not Determined

Decomposition temperature, °F: Not Determined Explosive Limits, %: Not Determined

Boiling Range, °F: > 100 °F Flash Point, °F: 54 ° F

Combustibility: Supports Combustion Auto-Ignition Temperature, °F: Not Determined Evaporation Rate: Vapor Pressure, mmHg: Not Determined

Vapor Density: Not Determined

N.I. = No Information

### 10. Stability and reactivity

STABILITY: Stable under normal conditions.

**CONDITIONS TO AVOID:** Heat, flames and sparks. **INCOMPATIBILITY:** Acids, Bases, Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Not determined.

### 11. Toxicological information



**Practical Experiences** 

**EMERGENCY OVERVIEW:** No Information

EFFECT OF OVEREXPOSURE - EYE CONTACT: No Information
EFFECT OF OVEREXPOSURE - INGESTION: No Information
EFFECT OF OVEREXPOSURE - INHALATION: No Information
EFFECT OF OVEREXPOSURE - SKIN CONTACT: No Information

**CARCINOGENICITY:** No Information

PRIMARY ROUTE(S) OF ENTRY:

**Skin Contact** 

**Acute Toxicity Values** 

The acute effects of this product have not been tested. Data on individual components are tabulated below

 CAS-No.
 Chemical Name
 Oral LD50
 Dermal LD50
 Vapor LC50

 67-63-0
 isopropanol
 1870 mg/kg Rat
 4059 mg/kg Rabbit
 72.6 mg/L Rat

Page 4 / 7 US\_GHS\_SDS (English)

34590-94-8	dipropylene glycol monomethyl ether	5230 mg/kg Rat	9500 mg/kg Rabbit	>20 mg/l
121-44-8	triethylamine	730 mg/kg Rat	580 mg/kg Rabbit	7.1 mg/L Rat
1333-86-4	carbon black	>5000 mg/kg Rat	>3000 mg/kg Rabbit	>20 mg/l
9005-00-9	polyethylene glycol octadecyl ether	1900 mg/kg Rat	N.I.	N.I.
64742-60-5	modified complex hydrocarbon	>5000 mg/kg Rat	>3600 mg/kg Rabbit	>20

N.I. = No Information

### 12. Ecological information

**ECOLOGICAL INFORMATION:** Ecological evaluation of this material has not been performed; however, do not allow the product to be released to the environment without governmental approval/permits.

### 13. Disposal Information



#### **Product**

**DISPOSAL METHOD:** Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Follow personal protective equipment recommendations found in Section VIII. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not allow the spilled product to enter public drainage system or open waterways.

### 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

**DOT:** NOT RESTRICTED

IATA: NOT RESTRICTED

IMDG: NOT RESTRICTED

### 15. Regulatory Information

### U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard

### **SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

CAS-No. **Chemical Name** octamethylcyclotetrasiloxane 556-67-2 mercury 7439-97-6

### U.S. State Regulations:

#### **CALIFORNIA PROPOSITION 65**



MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Carbon Black, Cancer, 0.1589% Toluene, Reproductive Harm, 0.0003%

### 16. Other Information

8/2/2023 **Revision Date:** 7/27/2024 Supersedes Date:

Reason for revision: **Product Composition Changed** 

Substance Hazardous Flag Changed

Substance and/or Product Properties Changed in Section(s):

01 - Product Information

02 - Hazards Identification 03 - Composition/Information on Ingredients

08 - Exposure Controls/Personal Protection 09 - Physical & Chemical Information 11 - Toxicological Information

15 - Regulatory Information 16 - Other Information Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health: 2 Flammability: Reactivity: 0 **Personal Protection:** X

#### Volatile Organic Compounds, gr/ltr: 345

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour. Self-heating: may catch fire. H251 H302 Harmful if swallowed. Toxic in contact with skin. H311

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

### Icons for GHS Pictograms shown in Section 3 describing each ingredient:

**GHS02** 





The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product where instructions and recommendations are not followed.

Only the original U.S. - English version is authoritative.