



NO BLUSH PLUS RETARDER

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

ACNB,FE733-001-1,M103-0 NO BLUSH PLUS RETARDER
475,M103-0475JPN

PRODUCT DESCRIPTION:

Contains a special solvent designed to eliminate blushing (hazy whiteness or cloudiness due to trapped moisture) in lacquer finishes.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Penetrating solvent retarder
Color	Clear
Sheen	N/A
Viscosity	N/A
WPG	6.500842470 lbs/gal
Solids by Volume	0.003039619 ±1%
Solids by Weight	0.003925170 ±1%
Flash Point	-76.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	778.939373859 g/l
Coating VOC (Lb/Gal)	6.500587300 lbs/gal
Material VOC (g/l)	778.939373810 g/l
Material VOC (Lb/Gal)	6.500587300 lbs/gal
#VOC/#Solid	25475.615378083 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	20.000009533
Spread Rate	0.048849002 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	To touch: 20 min, To package: overnight
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

DIRECTIONS:

SHAKE WELL for at least one minute after ball rattles. Can temperature should be between 65° and 90°F. Hold can 12 to 14 inches away from surface to be coated. Press spray button firmly. Spray in thin coats to avoid excessive drying times. Wait a few minutes to see if problem is solved before spraying another coat. Clean spray button after use by turning can upside down and pressing spray button until no more product comes out.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.