



FURNITURE CLEANER & RESTORER

TECHNICAL DATA SHEET

PRODUCT NUMBER

M107-0179

DESCRIPTION

FURNITURE CLEANER & RESTORER

PRODUCT DESCRIPTION:

Furniture Cleaner & Restorer maintains the original new look of oiled, walnut, teak and rosewood furniture. Instantly restores color as it cleans. Cleans and hides minor scratches on darker color wooden surfaces.

ADVANTAGES:

1. Restores color as it cleans
2. Hides scratches

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Solvent scratch cover
Color	Dark brown
Sheen	N/A
Viscosity	N/A
WPG	6.295800707 lbs/gal
Solids by Volume	2.471451147 ±1%
Solids by Weight	3.408394872 ±1%
Flash Point	-76.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	728.687662985 g/l
Coating VOC (Lb/Gal)	6.081214953 lbs/gal
Material VOC (g/l)	728.687662958 g/l
Material VOC (Lb/Gal)	6.081214953 lbs/gal
#VOC/#Solid	28.339323536 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	2.244754278
Spread Rate	39.642076398 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Hydrotreated Heavy Alkanes – CAS 64742-52-5 - solvent
C9-12 Light Alkanes – CAS 64742-88-7 - solvent
Petroleum Gases, Liquefied, Sweetened – CAS 68476-86-8 - propellant
Hydrotreated Light Alkanes – CAS 64742-47-8 - solvent
Toluene – CAS 108-88-3 - solvent
Asphalt, oxidized – CAS 64742-93-4 - colorant
m-Xylene - CAS 108-38-3 - solvent
o-Xylene – CAS 95-47-6 - solvent
p-Xylene – CAS 106-42-3 - solvent
Solvent Blue 79 – CAS 74499-36-8 - colorant
2,4-Bis[(Dimethylphenyl)Azo]-1,3-Benzenediol – CAS 29190-28-1 - colorant
Benzene – CAS 71-43-2 - not intentionally added
Dinonylnaphthalenesulfonic Acid – CAS 25322-17-2 - anti-static
Proprietary Anti-Static – CAS not available - anti-static

DIRECTIONS:

SHAKE WELL BEFORE USING. Make sure surface is free of dirt, grease, etc. Use drop cloth or newspapers to protect surrounding areas from spray mist. Apply sparingly to the surface, then wipe dry with a clean cloth. Ideal for walnut, maple, rosewood, teak and other fine oil-finished furniture. For best results, use only when can temperature is between 65° and 90°F. Clean spray button immediately after use by turning can upside down and pressing spray button for 5 seconds or until product ceases to evacuate the can.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.