



# WAX-WASH REMOVER AEROSOL

## TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M107-0190	WAX-WASH REMOVER AEROSOL

### PRODUCT DESCRIPTION:

Mohawk WAX WASH™ is a combination of solvents that removes wax, oil and foreign materials from most surfaces prior to applying a new finish or repair work of finished surfaces. WAX WASH™ is ideal for furniture, appliances, woodwork, and other finished surfaces.

### ADVANTAGES:

1. Removes wax, oil or foreign materials
2. Safe for most furniture finishes
3. Excellent prep solvent before repairs

### PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Solvent
Color	Clear
Sheen	N/A
Viscosity	N/A
WPG	5.991536664 lbs/gal
Solids by Volume	0.000000000 ±1%
Solids by Weight	0.000000000 ±1%
Flash Point	-76.000000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	717.941872334 g/l
Coating VOC (Lb/Gal)	5.991536664 lbs/gal
Material VOC (g/l)	717.941872300 g/l
Material VOC (Lb/Gal)	5.991536664 lbs/gal
#VOC/#Solid	0.000000000 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	0.000000000 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Water - CAS 7732-18-5 - solvent  
Isobutane - CAS 75-28-5 - propellant  
Dimethicone - CAS 63148-62-9 - surfactant  
Butane - CAS 106-97-8 - propellant  
Carnauba Wax - CAS 8015-86-9 - hydrophobe  
Benzoic acid, ammonium salt - CAS 1863-63-4 - corrosion inhibitor  
Methylparaben - CAS 99-76-3 - preservative  
d-Limonene - CAS 5989-27-5 - fragrance

Hydrocarbons, terpene processing by-products - CAS 68956-56-9 - fragrance  
Proprietary Rheology Modifier - CAS not available - rheology

---

#### DIRECTIONS:

1. Hold can 10 to 12 inches away and spray surface liberally. Wipe surface with a clean absorbent cloth.
2. Briskly wipe over surface, constantly revolving the cloth while wiping, so that wax and oils will absorb into the cloth rather than be redistributed on the surface.
3. Once the surface has been damp washed in the above manner, wipe off residue with a clean dry cloth and allow to dry for a few minutes before the application of a finish or before polishing. Use only as directed.

*The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.*

*Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.*

*It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.*

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.