



PENTHOUSE POLISH

TECHNICAL DATA SHEET

PRODUCT NUMBER

M107-0333

DESCRIPTION

PENTHOUSE POLISH

PRODUCT DESCRIPTION:

Penthouse® Furniture Polish is a high quality product for maintaining the beauty of the finish on fine furniture. Penthouse® will clean smears, smudges and prints while leaving a durable gloss wax protection. Also may be used on appliances, counter tops and stainless steel surfaces.

ADVANTAGES:

- Improved cleaning properties
- Better atomization, Improved fragrance
- Slightly different spray pattern
- Increased sheen

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Water base polish
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	7.647050183 lbs/gal
Solids by Volume	2.799428280 ±1%
Solids by Weight	3.054217970 ±1%
Flash Point	200.000000000 °F
HMIS	H: 1, F: 4, R: 0, P: X
Coating VOC (g/l)	492.592978702 g/l
Coating VOC (Lb/Gal)	4.110902298 lbs/gal
Material VOC (g/l)	108.386568023 g/l
Material VOC (Lb/Gal)	0.904532973 lbs/gal
#VOC/#Solid	3.872847840 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000003135
Spread Rate	44.902829611 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	7.8

Water - CAS 7732-18-5 - solvent
Isobutane - CAS 75-28-5 - propellant
Dimethicone - CAS 63148-62-9 - slip
Butane - CAS 106-97-8 - propellant
Carnauba Wax - CAS 8015-86-9 - hydrophobe
Benzoic acid, ammonium salt - CAS 1863-63-4 - corrosion inhibitor
Proprietary Fragrance - CAS not available - fragrance

Methylparaben - CAS 99-76-3 - preservative
Proprietary Rheology Modifier - CAS not available - rheology

DIRECTIONS:

SHAKE WELL BEFORE USING. For best results, use only when can temperature is between 65° and 90°F. Spray small amount into clean cloth and polish the surface. If product is sprayed directly on to the surface, wipe immediately. Do not allow polish to dry on surface.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.