

ARTISAN GLAZE MARKER AMARETTO CREAM

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M288-0001	ARTISAN GLAZE MARKER AMARETTO CREAM

PRODUCT DESCRIPTION:

The new Artisan Glaze Marker is used to create glaze lines on a glazed cabinet or furniture part. This Artisan Glaze marker can be used to add to or alter an existing glaze line.

This new marker formulation allows you to apply the glaze line to the part and then work the line to blend in to the surrounding glaze effect. This touch-up marker was designed to be the same strength as a light glaze, dry slowly, which enables you to work color once it is applied to the part and build color over itself. You can add, alter or create a glaze line over a finish using this marker. This marker is designed to be used in the field, shop or factory settings.

ADVANTAGES:

- 1. Quick and easy to use
- 2. Can be used during or after your finishing process
- 3. Can be used to create or touch-up existing glaze lines
- 4. 6 Stock colors AND a 6-pack assortment
- 5. Custom colors available

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Solvent based marker
Color	Amaretto Cream
Sheen	Not specified
Viscosity	27" ± 1 Zahn #1 sig @ 77° F
WPG	7.609416794 lbs/gal
Solids by Volume	13.457389570 ±1%
Solids by Weight	19.608841227 ±1%
Flash Point	-4.000000000 °F
HMIS	H: 2, F: 3, R: 0, P: X
Coating VOC (g/I)	729.944815381 g/l
Coating VOC (Lb/Gal)	6.091713295 lbs/gal
Material VOC (g/I)	697.670362912 g/l
Material VOC (Lb/Gal)	5.822368381 lbs/gal
#VOC/#Solid	3.902081871 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	1.226073089
Spread Rate	215.855034849 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	To touch: 5 min, To handle or recoat: 10 min.
Oven Dry	N/A
Shelf-Life (Unopened)	24 months

Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

DIRECTIONS:

Shake the marker to mix the color. Depress the tip with the pen in the upright position to relieve pressure in the marker. Depress the tip with the pen in the marking position (a wet tip will give you a wide line, a drier tip will give you a cleaner thinner line). Draw the line that you desire on the cabinet or furniture part.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.