

WATERBORNE WHITE SEALER 5 GAL

TECHNICAL DATA SHEET

PRODUCT NUMBER DESCRIPTION

M640-1067,M640-1068 WATERBORNE WHITE SEALER 5 GAL

PRODUCT DESCRIPTION:

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology N/A Color N/A Sheen N/A Viscosity N/A WPG 11.798058885 lbs/gal Solids by Volume 32.952147637 ±1% Solids by Weight 52.705716262 ±1% Flash Point 200.000000000 °F HMIS H: 1, F: 1, R: 0, P: X Coating VOC (g/l) 86.606146462 g/l Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
Sheen N/A Viscosity N/A WPG 11.798058885 lbs/gal Solids by Volume 32.952147637 ±1% Solids by Weight 52.705716262 ±1% Flash Point 200.000000000 °F HMIS H: 1, F: 1, R: 0, P: X Coating VOC (g/I) 86.606146462 g/I Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
Viscosity N/A WPG 11.798058885 lbs/gal Solids by Volume 32.952147637 ±1% Solids by Weight 52.705716262 ±1% Flash Point 200.000000000 °F HMIS H: 1, F: 1, R: 0, P: X Coating VOC (g/l) 86.606146462 g/l Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
WPG 11.798058885 lbs/gal Solids by Volume 32.952147637 ±1% Solids by Weight 52.705716262 ±1% Flash Point 200.000000000 °F HMIS H: 1, F: 1, R: 0, P: X Coating VOC (g/l) 86.606146462 g/l Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
Solids by Volume 32.952147637 ±1% Solids by Weight 52.705716262 ±1% Flash Point 200.000000000 °F HMIS H: 1, F: 1, R: 0, P: X Coating VOC (g/I) 86.606146462 g/I Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
Solids by Weight 52.705716262 ±1% Flash Point 200.000000000 °F HMIS H: 1, F: 1, R: 0, P: X Coating VOC (g/I) 86.606146462 g/I Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
Flash Point 200.000000000 °F HMIS H: 1, F: 1, R: 0, P: X Coating VOC (g/l) 86.606146462 g/l Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
HMIS H: 1, F: 1, R: 0, P: X Coating VOC (g/I) 86.606146462 g/I Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
Coating VOC (g/l) 86.606146462 g/l Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
Coating VOC (Lb/Gal) 0.722765898 lbs/gal	
M + : 1,1/00 / //)	
Material VOC (g/l) 31.485187025 g/l	
Material VOC (Lb/Gal) 0.262757557 lbs/gal	
#VOC/#Solid 0.042255859 lbs/lbs solid	
VHAP Ratio (#VHAP/#Solid) 0.001646193	
Spread Rate 528.552448097 sq. ft./gal @ 1.0 mil DFT (no loss)	
Catalyst/Ratio N/A	
Reducer N/A	
Retarder N/A	
AirDry N/A	
Oven Dry N/A	
Shelf-Life (Unopened) 12 months	
Pot-Life (Catalyzed) N/A	
Recoat Instruction N/A	
PH 8.30 - 8.70	

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.