



8XLEMON OIL POLISH GAL

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

B820-3864PLSM,M820-2002 8XLEMON OIL POLISH GAL
,M820-2004,M820-2005,M820-2007

PRODUCT DESCRIPTION:

Lemon Oil Polish is used for all types of furniture, paneling, and interior woodwork. Lemon Oil Polish is a longtime favorite among craftsmen and antique restorers because of its citrus smell and ability to revive old worn finishes.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Oil Polish
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	7.518962141 lbs/gal
Solids by Volume	1.669385026 ±1%
Solids by Weight	1.778570489 ±1%
Flash Point	255.200000000 °F
HMIS	H: 1, F: 1, R: 0, P: X
Coating VOC (g/l)	884.943608739 g/l
Coating VOC (Lb/Gal)	7.385231681 lbs/gal
Material VOC (g/l)	884.942734621 g/l
Material VOC (Lb/Gal)	7.385224385 lbs/gal
#VOC/#Solid	55.224871503 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.021511039
Spread Rate	26.776910474 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	24 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

Hydrotreated Heavy Alkanes - CAS 64742-52-5 - solvent
Proprietary Fragrance - CAS not available - fragrance
Proprietary Surfactant - CAS not available - surfactant
Chromate(1-), bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]-, hydrogen - CAS 5601-29-6 - colorant
Dinonylnaphthalenesulfonic Acid - CAS 25322-17-2 - anti-static
Proprietary Anti-Static - CAS not available - anti-static
Benzene - CAS 71-43-2 - not intentionally added

DIRECTIONS:

SHAKE WELL BEFORE USING. Apply Lemon Oil Polish to cloth and apply to surface. Wipe dry with another cloth.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.