



LEATHER GUARD PROTECTOR

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M850-10034	LEATHER GUARD PROTECTOR

PRODUCT DESCRIPTION:

Leather Protector is a highly advanced product designed to assist leather in repelling water, oil and alcohol based stains. It is perfectly suited for natural grained leather because it doesn't change the feel or the color of even these sensitive leathers while adding stain resistance. For topcoated leather, the application of Leather Protector will ease the removal of difficult stains like ink, lipstick, mustard, newspaper print, and blue jean transfer. Leather Protector forms a transparent, breathable barrier that will improve stain resistance and efficiency of cleaning.

ADVANTAGES:

1. PFSA Free

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.349882793 lbs/gal
Solids by Volume	1.614399552 ±1%
Solids by Weight	1.700042391 ±1%
Flash Point	200.000000000 °F
HMIS	H: 2, F: 1, R: 0, P: X
Coating VOC (g/l)	133.331545766 g/l
Coating VOC (Lb/Gal)	1.112709644 lbs/gal
Material VOC (g/l)	2.587568777 g/l
Material VOC (Lb/Gal)	0.021594075 lbs/gal
#VOC/#Solid	0.152122856 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	25.894597055 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	5.4
Contains UV Absorber	

Water - CAS 7732-18-5 - solvent
Proprietary Resin - CAS Not Available - resin
Isopropanol - CAS 67-63-0 solvent
Hydroxyethylcellulose - 9004-62-0 - thickener
Benzophenone-4 - CAS 4065-45-6 - UV absorber

DIRECTIONS:

Directions: Shake well. Pre-test onto a hidden area. If darkening occurs, do not use. Dampen a lint free cloth with Leather Protector and wipe on evenly. Allow to dry. If a higher gloss is desired, buff with a soft lint free cloth. Leather Cleaner (M850-10014) and Leather Protector should be used regularly for cleaning and protection.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.