

PRIMER SEALER GRAY

	PRODUCT NUMBER
ECHNICAL DATA CHEET	

DESCRIPTION

M103-0457

PRIMER SEALER GRAY

PRODUCT DESCRIPTION:

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Color Gray Sheen N/A Viscosity N/A WPG 6.990107169 lbs/gal Solids by Volume 8.906857627 ±1% Solids by Weight 20.827268401 ±1% Flash Point -76.000000000°F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 606.072098038 g/l Coating VOC (gl/l) 5.057941027 lbs/gal Material VOC (gl/l) 427.112205435 g/l Material VOC (lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratic (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Technology	pigmented, stearated nitrocellulose primer
Viscosity N/A WPG 6.990107169 lbs/gal Solids by Volume 8.906857627 ±1% Solids by Weight 20.827268401 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 606.072098038 g/l Coating VOC (Lb/Gal) 5.057941027 lbs/gal Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Color	Gray
WPG 6.990107169 lbs/gal Solids by Volume 8.906857627 ± 1% Solids by Weight 20.827268401 ± 1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 606.072098038 g/l Coating VOC (Lb/Gal) 5.057941027 lbs/gal Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Sheen	N/A
Solids by Volume 8.906857627 ±1% Solids by Weight 20.827268401 ±1% Flash Point -76.00000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 606.072098038 g/l Coating VOC (Lb/Gal) 5.057941027 lbs/gal Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Viscosity	N/A
Solids by Weight 20.827268401 ±1% Flash Point -76.00000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 606.072098038 g/l Coating VOC (Lb/Gal) 5.057941027 lbs/gal Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	WPG	6.990107169 lbs/gal
Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 606.072098038 g/l Coating VOC (Lb/Gal) 5.057941027 lbs/gal Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Volume	8.906857627 ±1%
HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 606.072098038 g/l Coating VOC (Lb/Gal) 5.057941027 lbs/gal Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Weight	20.827268401 ±1%
Coating VOC (g/l) 606.072098038 g/l Coating VOC (Lb/Gal) 5.057941027 lbs/gal Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Flash Point	-76.000000000 °F
Coating VOC (Lb/Gal) 5.057941027 lbs/gal Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	HMIS	H: 2, F: 4, R: 0, P: X
Material VOC (g/l) 427.112205435 g/l Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (g/I)	606.072098038 g/l
Material VOC (Lb/Gal) 3.564439893 lbs/gal #VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (Lb/Gal)	5.057941027 lbs/gal
#VOC/#Solid 2.448359279 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.149461839 Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (g/l)	427.112205435 g/l
VHAP Ratio (#VHAP/#Solid)0.149461839Spread Rate142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss)Catalyst/RatioN/AReducerN/ARetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Material VOC (Lb/Gal)	3.564439893 lbs/gal
Spread Rate 142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	#VOC/#Solid	2.448359279 lbs/lbs solid
Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	VHAP Ratio (#VHAP/#Solid)	0.149461839
Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Spread Rate	142.865996337 sq. ft./gal @ 1.0 mil DFT (no loss)
RetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Catalyst/Ratio	N/A
AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Reducer	N/A
Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Retarder	N/A
Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	36 months
	Pot-Life (Catalyzed)	N/A
PH N/A	Recoat Instruction	N/A
	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.