

CAB PIGMENTED FINISH RED

PRODUCT NUMBER

DESCRIPTION

M115-3001

CAB PIGMENTED FINISH RED

PRODUCT DESCRIPTION:

TECHNICAL DATA SHEET

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Color N/A Sheen N/A Viscosity N/A WPG 6.700988147 lbs/gal Solids by Volume 7.614224367 ±1% Solids by Weight 12.174885096 ±1% Flash Point -76.00000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 698.096114771 g/l Coating VOC (g/l) 698.096114771 g/l Coating VOC (g/l) 649.497060032 g/l Material VOC (g/l) 649.497060032 g/l Material VOC (tb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Technology	N/A
Viscosity N/A WPG 6.700988147 lbs/gal Solids by Volume 7.614224367 ±1% Solids by Weight 12.174885096 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 698.096114771 g/l Coating VOC (Lb/Gal) 5.825915200 lbs/gal Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Ni/A N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Color	N/A
WPG 6.700988147 lbs/gal Solids by Volume 7.614224367 ±1% Solids by Weight 12.174885096 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 698.096114771 g/l Coating VOC (Lb/Gal) 5.825915200 lbs/gal Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Sheen	N/A
Solids by Volume 7.614224367 ±1% Solids by Weight 12.174885096 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 698.096114771 g/l Coating VOC (Lb/Gal) 5.825915200 lbs/gal Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Viscosity	N/A
Solids by Weight 12.174885096 ±1% Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 698.096114771 g/l Coating VOC (Lb/Gal) 5.825915200 lbs/gal Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	WPG	6.700988147 lbs/gal
Flash Point -76.000000000 °F HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 698.096114771 g/l Coating VOC (Lb/Gal) 5.825915200 lbs/gal Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Volume	7.614224367 ±1%
HMIS H: 2, F: 4, R: 0, P: X Coating VOC (g/l) 698.096114771 g/l Coating VOC (Lb/Gal) 5.825915200 lbs/gal Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Weight	12.174885096 ±1%
Coating VOC (g/l) 698.096114771 g/l Coating VOC (Lb/Gal) 5.825915200 lbs/gal Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Flash Point	-76.000000000 °F
Coating VOC (Lb/Gal) 5.825915200 lbs/gal Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	HMIS	H: 2, F: 4, R: 0, P: X
Material VOC (g/l) 649.497060032 g/l Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (g/I)	698.096114771 g/l
Material VOC (Lb/Gal) 5.420334986 lbs/gal #VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (Lb/Gal)	5.825915200 lbs/gal
#VOC/#Solid 6.643889594 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (g/l)	649.497060032 g/l
VHAP Ratio (#VHAP/#Solid) 0.520201802 Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (Lb/Gal)	5.420334986 lbs/gal
Spread Rate 122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	#VOC/#Solid	6.643889594 lbs/lbs solid
Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	VHAP Ratio (#VHAP/#Solid)	0.520201802
Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Spread Rate	122.132158847 sq. ft./gal @ 1.0 mil DFT (no loss)
RetarderN/AAirDryN/AOven DryN/AShelf-Life (Unopened)36 monthsPot-Life (Catalyzed)N/ARecoat InstructionN/A	Catalyst/Ratio	N/A
AirDry N/A Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Reducer	N/A
Oven Dry N/A Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Retarder	N/A
Shelf-Life (Unopened) 36 months Pot-Life (Catalyzed) N/A Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	36 months
	Pot-Life (Catalyzed)	N/A
PH N/A	Recoat Instruction	N/A
	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.