



WIPING WOOD STAIN AEROSOL TOASTED ALMOND

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M145-001	WIPING WOOD STAIN AEROSOL TOASTED ALMOND

PRODUCT DESCRIPTION:

This product is designed to match color and/or sheen of wood projects. Aerosol Stain is a pigment stain that will beautifully color wood and enhance the natural grain. Can be used with any finish. Resists fading from UV rays.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Solvent base wiping wood stain
Color	BROWN
Sheen	N/A
Viscosity	N/A
WPG	7.079698795 lbs/gal
Solids by Volume	19.154197954 ±1%
Solids by Weight	34.969486674 ±1%
Flash Point	-68.800000000 °F
HMIS	H: 2, F: 4, R: 0, P: X
Coating VOC (g/l)	551.657088684 g/l
Coating VOC (Lb/Gal)	4.603846700 lbs/gal
Material VOC (g/l)	551.641213091 g/l
Material VOC (Lb/Gal)	4.603714209 lbs/gal
#VOC/#Solid	1.859538916 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.009075426
Spread Rate	307.231239989 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	To touch: 5 minutes; To handle: 10 minutes; To topcoat: 30 - 45 minutes
Oven Dry	User specific
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

DIRECTIONS:

Shake for one minute before application and regularly during long use. Apply stain generously. Spread evenly by wiping or brushing. Allow to flash off momentarily, and then use a clean absorbent cloth to remove excess. Dry (approximately 30 minutes) before sealing or topcoating. Clean nozzle by inverting the can and depressing the spray tip for 5 seconds.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.