

FIL-STIK NUTMEG/CHERRY

PRODUCT NUMBER

DESCRIPTION

M230-4008

FIL-STIK NUTMEG/CHERRY

PRODUCT DESCRIPTION:

TECHNICAL DATA SHEET

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology N/A Color N/A Sheen N/A Viscosity N/A WPG 7.970078579 lbs/gal Solids by Volume 100.000000000±1% Solids by Weight 100.000000000 °F HMIS H: 2, F: 0, R: 0, P: X Coating VOC (g/l) 0.000000000 g/l Coating VOC (lb/Gal) 0.000000000 g/l Material VOC (g/l) 0.000000000 g/l Material VOC (b/Gal) 0.000000000 lbs/gal #VOC/#Solid 0.000000000 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) N/A Pot-Life (Catalyzed) N/A Recoat Instruction N/A		
Sheen N/A Viscosity N/A WPG 7.970078579 lbs/gal Solids by Volume 100.00000000 ±1% Solids by Weight 100.00000000 ±1% Flash Point 320.000000000 °F HMIS H: 2, F: 0, R: 0, P: X Coating VOC (g/l) 0.00000000 g/l Coating VOC (Lb/Gal) 0.00000000 g/l Material VOC (g/l) 0.00000000 lbs/gal Material VOC (Lb/Gal) 0.000000000 lbs/gal #VOC/#Solid 0.000000000 lbs/gbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A AirDry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Technology	N/A
Viscosity N/A WPG 7.970078579 lbs/gal Solids by Volume 100.000000000 ±1% Solids by Weight 100.000000000 °F Flash Point 320.000000000 °F HMIS H: 2, F: 0, R: 0, P: X Coating VOC (g/l) 0.00000000 g/l Coating VOC (Lb/Gal) 0.00000000 lbs/gal Material VOC (g/l) 0.00000000 lbs/gal #VOC/#Solid 0.00000000 lbs/gbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Color	N/A
WPG 7.970078579 lbs/gal Solids by Volume 100.000000000 ±1% Solids by Weight 100.000000000 ±1% Flash Point 320.000000000 °F HMIS H: 2, F: 0, R: 0, P: X Coating VOC (g/l) 0.000000000 g/l Coating VOC (Lb/Gal) 0.000000000 lbs/gal Material VOC (g/l) 0.000000000 lbs/gal #VOC/#Solid 0.00000000 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.00000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Sheen	N/A
Solids by Volume 100.000000000 ±1% Solids by Weight 100.000000000 ±1% Flash Point 320.000000000 °F HMIS H: 2, F: 0, R: 0, P: X Coating VOC (g/l) 0.000000000 g/l Coating VOC (Lb/Gal) 0.000000000 lbs/gal Material VOC (b/Gal) 0.000000000 lbs/gal #VOC/#Solid 0.000000000 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Recoat Instruction N/A	Viscosity	N/A
Solids by Weight 100.000000000 ±1% Flash Point 320.000000000 °F HMIS H: 2, F: 0, R: 0, P: X Coating VOC (g/l) 0.000000000 g/l Coating VOC (Lb/Gal) 0.000000000 lbs/gal Material VOC (g/l) 0.000000000 lbs/gal #VOC/#Solid 0.000000000 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	WPG	7.970078579 lbs/gal
Flash Point 320.000000000 °F HMIS H: 2, F: 0, R: 0, P: X Coating VOC (g/l) 0.00000000 g/l Coating VOC (Lb/Gal) 0.000000000 lbs/gal Material VOC (g/l) 0.000000000 g/l Material VOC (Lb/Gal) 0.000000000 lbs/gal #VOC/#Solid 0.000000000 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Volume	100.000000000 ±1%
HMIS H: 2, F: 0, R: 0, P: X Coating VOC (g/I) 0.000000000 g/I Coating VOC (Lb/GaI) 0.000000000 g/I Material VOC (g/I) 0.000000000 g/I Material VOC (Lb/GaI) 0.000000000 lbs/gaI #VOC/#Solid 0.000000000 VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.0000000000 sq. ft./gaI @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Solids by Weight	100.000000000 ±1%
Coating VOC (g/I) 0.000000000 g/I Coating VOC (Lb/Gal) 0.000000000 lbs/gal Material VOC (g/I) 0.000000000 g/I Material VOC (Lb/Gal) 0.000000000 lbs/gal #VOC/#Solid 0.000000000 VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.0000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Flash Point	320.000000000 °F
Coating VOC (Lb/Gal) 0.000000000 lbs/gal Material VOC (g/l) 0.000000000 g/l Material VOC (Lb/Gal) 0.000000000 lbs/gal #VOC/#Solid 0.0000000000 VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	HMIS	H: 2, F: 0, R: 0, P: X
Material VOC (g/l) 0.000000000 g/l Material VOC (Lb/Gal) 0.000000000 lbs/gal #VOC/#Solid 0.000000000 VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.0000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (g/I)	0.000000000 g/l
Material VOC (Lb/Gal) 0.000000000 lbs/gal #VOC/#Solid 0.000000000 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Coating VOC (Lb/Gal)	0.00000000 lbs/gal
#VOC/#Solid 0.00000000 lbs/lbs solid VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (g/l)	0.000000000 g/l
VHAP Ratio (#VHAP/#Solid) 0.000000000 Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Material VOC (Lb/Gal)	0.000000000 lbs/gal
Spread Rate 1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss) Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	#VOC/#Solid	0.00000000 lbs/lbs solid
Catalyst/Ratio N/A Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	VHAP Ratio (#VHAP/#Solid)	0.00000000
Reducer N/A Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Spread Rate	1604.000000000 sq. ft./gal @ 1.0 mil DFT (no loss)
Retarder N/A AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Catalyst/Ratio	N/A
AirDry N/A Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Reducer	N/A
Oven Dry N/A Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Retarder	N/A
Shelf-Life (Unopened) NA Pot-Life (Catalyzed) N/A Recoat Instruction N/A	AirDry	N/A
Pot-Life (Catalyzed) N/A Recoat Instruction N/A	Oven Dry	N/A
Recoat Instruction N/A	Shelf-Life (Unopened)	NA
	Pot-Life (Catalyzed)	N/A
PH N/A	Recoat Instruction	N/A
	PH	N/A

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.