

## ULTRA® MARK GREYLOFT W/SABLE 9731200B66M/FLAGSTONE SWP/STERL

## TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M280-4250

ULTRA® MARK GREYLOFT W/SABLE 9731200B66M/FLAGSTONE SWP/STERL

PRODUCT DESCRIPTION:

N/A

## PHYSICAL PROPERTIES AND SPECIFICATIONS

A A A A D70974321 lbs/gal .863711381 ±1% .961633866 ±1% .40000000 °F 2, F: 3, R: 0, P: X 3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal 378905389 lbs/lbs solid
A A 970974321 lbs/gal .863711381 ±1% .961633866 ±1% .40000000 °F 2, F: 3, R: 0, P: X 3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l
A 970974321 lbs/gal .863711381 ±1% .961633866 ±1% .40000000 °F 2, F: 3, R: 0, P: X 3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal
270974321 lbs/gal .863711381 ±1% .961633866 ±1% .40000000 °F 2, F: 3, R: 0, P: X 3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal
.863711381 ±1% .961633866 ±1% .400000000 °F 2, F: 3, R: 0, P: X 3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal
.961633866 ±1% .40000000 °F 2, F: 3, R: 0, P: X 3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal
.40000000 °F 2, F: 3, R: 0, P: X 3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal
2, F: 3, R: 0, P: X 3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal
3.172390455 g/l 200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal
200644188 lbs/gal 1.981596230 g/l 190706493 lbs/gal
1.981596230 g/l 190706493 lbs/gal
90706493 lbs/gal
378905389 lbs/lbs solid
014435516
2.773930551 sq. ft./gal @ 1.0 mil DFT (no loss)
Α
Α
Α.
Α
A
months
A
Α
4

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.