



WATERBORNE PRE-CATALYZED LACQUER SATIN 40 SHEEN GAL

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M640-21407	WATERBORNE PRE-CATALYZED LACQUER SATIN 40 SHEEN GAL

PRODUCT DESCRIPTION:

N/A

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Waterborne
Color	Clear
Sheen	40 +/-2 @ 5 wet mils applied
Viscosity	25 +/- 2 seconds #3 Signature Zahn Cup
WPG	8.657728799 lbs/gal
Solids by Volume	31.699767388 ±1%
Solids by Weight	34.148604667 ±1%
Flash Point	200.000000000 °F
HMIS	H: 2, F: 1, R: 0, P: X
Coating VOC (g/l)	209.643657495 g/l
Coating VOC (Lb/Gal)	1.749567352 lbs/gal
Material VOC (g/l)	86.040544408 g/l
Material VOC (Lb/Gal)	0.718045703 lbs/gal
#VOC/#Solid	0.242870713 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.030712406
Spread Rate	508.464268904 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	None
Reducer	Ready to spray- Add water if weeded
Retarder	Up to 4 oz/Gal Texanol if needed for open time
AirDry	Use over A28C3500 Sealer, or as self-seal
Oven Dry	Customer Specific
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	Dry Minimum 1 hour. Scuff Sand with 320 Grit Prior To Recoat
PH	8

1 Freeze/thaw cycle. If product freezes, allow 48-72 hours to recover.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.