



# 8XWAX WASH™ REMOVER GAL

## TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
M712-1907	8XWAX WASH™ REMOVER GAL

### PRODUCT DESCRIPTION:

Mohawk™ Wax Wash™ is a combination of solvents which will remove wax, oil and foreign materials from most surfaces in one application. The presence of wax, oil or foreign material can retard drying or cause defects in finishing topcoats. Prior to applying a new finish or repair, clean surface with Wax Wash™. Ideal for furniture, appliances, woodwork, and other finished surfaces.

### ADVANTAGES:

1. Removes wax, oil or foreign materials
2. Safe for most furniture finishes
3. Excellent prep solvent before repairs

### PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Solvent
Color	Clear
Sheen	N/A
Viscosity	N/A
WPG	6.752886480 lbs/gal
Solids by Volume	0.000000000 ±1%
Solids by Weight	0.000000000 ±1%
Flash Point	39.200000000 °F
HMIS	H: 2, F: 3, R: 0, P: X
Coating VOC (g/l)	809.171375399 g/l
Coating VOC (Lb/Gal)	6.752886480 lbs/gal
Material VOC (g/l)	809.171375352 g/l
Material VOC (Lb/Gal)	6.752886480 lbs/gal
#VOC/#Solid	0.000000000 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	0.000000000 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

C9-12 Light Alkanes - CAS 64742-88-7 - solvent  
Toluene - CAS 108-88-3 - solvent  
Hydrotreated Light Alkanes - CAS 64742-47-8 - solvent  
Benzene - CAS 71-43-2 - not intentionally added

---

**DIRECTIONS:**

Fold a clean, absorbent cloth into several layers and then saturate the cloth with Wax Wash™. Briskly wipe over surface, constantly turning the cloth while wiping, so that wax or oils will absorb into the cloth rather than be redistributed on the surface. Once the surface has been damp washed in the above manner, wipe off residue with a clean dry cloth and allow to dry for a few minutes before the application of a finish or before repolishing.

*The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.*

*Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.*

*It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.*

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.