



WIPING STAIN CLEAR BASE, 29 OZ.

TECHNICAL DATA SHEET

PRODUCT NUMBER	DESCRIPTION
MA240-50006	WIPING STAIN CLEAR BASE, 29 OZ.

PRODUCT DESCRIPTION:

Mohawk Architectural Wiping Stain Clear Base can be used as a stain base to dilute the color of an MA240-series stain color without changing the way it works and dries or increasing the VOC's. Use as a clear base and add colorants to make a custom stain colors. Use as a pre-stain conditioner to control stain color penetration and development.

ADVANTAGES:

1. Short filled to allow user to add colorants to make custom colors
2. Good open, working time...EASY TO USE!
3. VOC compliant ANYWHERE IN THE COUNTRY for SHOP or ON SITE application!

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	Oil based wiping stain base
Color	Clear
Sheen	N/A
Viscosity	N/A
WPG	7.434083353 lbs/gal
Solids by Volume	55.265827767 ±1%
Solids by Weight	59.045949250 ±1%
Flash Point	-4.000000000 °F
HMIS	H: 2, F: 3, R: 0, P: X
Coating VOC (g/l)	210.705670156 g/l
Coating VOC (Lb/Gal)	1.758430309 lbs/gal
Material VOC (g/l)	155.711462321 g/l
Material VOC (Lb/Gal)	1.299479765 lbs/gal
#VOC/#Solid	0.296041084 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.018025380
Spread Rate	886.463877383 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	To touch: 10 minutes, To handle: 20 minutes, To topcoat: 60 minutes
Oven Dry	N/A
Shelf-Life (Unopened)	36 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	N/A

DIRECTIONS:

Use before staining to reduce blotchy areas in soft woods. Sand wood with 150 or 180 grit sandpaper. Apply by spray, brush or rag liberally over surface and remove excess by wiping with a cloth. Allow to dry 15-30 minutes before applying Mohawk Architectural Wiping Stain color. For best results apply stain within 12 hours. Wiping Stain Clear Base may also be used to reduce the color of any Mohawk Architectural 240 VOC Wiping Stain (MA240-series) color.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Wood Finishes Group, Inc.; P.O. Box 22000 Hickory, NC 28603; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.