



MICROFIBER CLEANER 8 OZ

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M850-10054

MICROFIBER CLEANER 8 OZ

PRODUCT DESCRIPTION:

MICROFIBER CLEANER - Solvent-free cleaner designed to delicately and efficiently clean microfiber fabrics. Removes dirt and water-based or greasy stains from microfiber furniture. Leather Type Usage: Microfiber Only! Description: Removes dirt and water based or greasy stains.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.307701455 lbs/gal
Solids by Volume	0.667544166 ±1%
Solids by Weight	0.809588221 ±1%
Flash Point	200.000000000 °F
HMIS	H: 1, F: 1, R: 0, P: X
Coating VOC (g/l)	390.986713265 g/l
Coating VOC (Lb/Gal)	3.262953894 lbs/gal
Material VOC (g/l)	8.845169480 g/l
Material VOC (Lb/Gal)	0.073816780 lbs/gal
#VOC/#Solid	1.097513915 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	10.707408423 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	6.5

Water - CAS 7732-18-5 - solvent
Proprietary Surfactant - CAS Not Available - surfactant
Proprietary Defoamer - CAS Not Available - defoamer

DIRECTIONS:

Shake well. Pre-test onto a hidden area. Dampen a white cloth with product and lightly rub. If color is transferred, do not use. Also be sure no rings are left after drying. Before application, remove loose dirt with non-abrasive absorbent cloth. Use an upward swiping motion, being careful not to push stain deeper inside Microfiber. Apply directly to a sponge and squeeze to create foam. Gently rub foam into Microfiber. Repeat if necessary. After drying, lightly brush the area with a Reviving Sponge

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.