



LEATHER CLEANER 4 OZ

TECHNICAL DATA SHEET

PRODUCT NUMBER

DESCRIPTION

M850-10014,M850-1019,M8 51-10017,M898-86123 LEATHER CLEANER 4 OZ

PRODUCT DESCRIPTION:

Leather Cleaner is water based, 100% non-solvent cleaner designed to clean gently but thoroughly, without harming the natural beauty and feel of the leather. It is formulated specifically for grained leathers; those with a topcoat as well as natural aniline leathers. Leather Cleaner will clean general soiling as well as water based and protein based stains from leather. Leather Cleaner is most effective when used in combination with a sponge. The sponge absorbs soiling while preventing excessive rubbing on the leather's surface. Leather Cleaner is designed to keep cleaning residue to a minimum. This residue, left by most cleaning solutions, can harm the leather's flexibility characteristics and reduce wet rub resistance over time.

PHYSICAL PROPERTIES AND SPECIFICATIONS

Technology	N/A
Color	N/A
Sheen	N/A
Viscosity	N/A
WPG	8.365609343 lbs/gal
Solids by Volume	0.941155744 ±1%
Solids by Weight	1.113216701 ±1%
Flash Point	200.000000000 °F
HMIS	H: 2, F: 1, R: 0, P: X
Coating VOC (g/l)	133.321792070 g/l
Coating VOC (Lb/Gal)	1.112628245 lbs/gal
Material VOC (g/l)	1.489956146 g/l
Material VOC (Lb/Gal)	0.012429204 lbs/gal
#VOC/#Solid	0.133519638 lbs/lbs solid
VHAP Ratio (#VHAP/#Solid)	0.000000000
Spread Rate	15.096138134 sq. ft./gal @ 1.0 mil DFT (no loss)
Catalyst/Ratio	N/A
Reducer	N/A
Retarder	N/A
AirDry	N/A
Oven Dry	N/A
Shelf-Life (Unopened)	12 months
Pot-Life (Catalyzed)	N/A
Recoat Instruction	N/A
PH	6.7
Contains UV Absorber	

Water - CAS 7732-18-5 - solvent
DL-Aspartic acid, N-(3-carboxy-1-oxo-3-sulfopropyl)-N-octadecyl-, tetrasodium salt - CAS 38916-42-6 - surfactant
Methylparaben - CAS 99-76-3 - preservative
Benzophenone-4 - CAS 4065-45-6 - UV absorber
1-Propanaminium, 3-(dodecyloxy)-2-hydroxy-N,N-bis(2-hydroxyethyl)-N-methyl-, methyl sulfate (salt) - CAS 18602-17-0 - anti-static
Proprietary Defoamer - CAS Not Available - defoamer

DIRECTIONS:

Directions: Shake well. Pre-test onto a hidden area. Apply with a white cloth. If color transfers to the cloth or a mark is left after drying, do not use. Apply to a sponge and squeeze to create foam, gently rub into leather. Repeat as needed. Allow to air dry or use a hair dryer to speed drying. Leather Cleaner and Leather Protector (M850-1006) should be used regularly for cleaning and protection.

The data on this sheet are calculated values (as formulated) and will not represent exact values for every product. For Safety and Other Precautions, read the SDS before using the product. SDS are available upon request. If Safety Data Sheet is required, contact: Mohawk Finishing Products, a Division of RPM Industrial Coatings Group, Inc.; 3194 B Hickory Blvd, Hudson, NC 28638; Phone: 1-800-545-0047; Fax: 1-800-721-1545.

Drying times and viscosities reported are as tested under laboratory conditions (77°F (25°C)) with relative humidity of approximately 45%. Changes in temperature and humidity will affect product data.

It is the user's responsibility to verify product compliance with all applicable regulations or permits before proceeding with use. Always pretest any finishing products to verify suitability to the desired use before proceeding with any application. Manufacturer makes no warranties, express or implied, including (but not limited to) warranties of merchantability and fitness for particular purposes. Manufacturer will not be liable for any incidental, consequential or special damages or losses derived, directly or indirectly, from or as a consequence of purchaser's use of this product.

TDS. Mohawk Finishing Products, Division of RPM Wood Finishes Group, Inc. All rights reserved.