

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Mohawk C.A.B Blender Flow-Out™ Aerosol

M103-0325 Matte 25 sheen, M103-0340 Satin 40 sheen

13oz aerosol

Product Description: Mohawk C.A.B Blender Flow-Out™ aerosol is designed to blend the spray line of a C.A.B. opaque aerosol. This product contains a blending formula that is ideal for blending spray lines, blending in overspray and minor surface scratches in C.A.B. lacquer finishes.

Advantages:

1. Blend the edge of a spray line into the rest of the finish
2. Creates a uniform sheen
3. Available in matte & Satin Sheens
4. Non-yellowing

Characteristics:

Weight per gallon: 6.49 lbs*

Solids % (wt): 2.67*

Solids % (vol): 1.80*

Package viscosity: 24 secs. Zahn #1 sig

Dry time: Air dry @ 77 F, 50% relative humidity

To touch: 15 min

To handle: 30 min

To recoat: 45 min

PWR category: WTR

PWR Category limit: 1.50

PWR of product: 1.017 *

VOC's (coating): 6.30 lbs/gal (754.45 g/l)*

VOC's (material): 5.80 lbs/gal (694.87 g/l)*

VHAP's: 2.74 lbs VHAP's/lb solids*

Package life: 3 years

*Includes propellant; values vary between sheens

All values theoretical; not intended to be exact QC specifications.

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection - X

Directions: SHAKE WELL for at least one minute after ball rattles. Can temperature should be between 55° and 90°F. Hold can 12 to 14 inches away from surface to be coated, press spray button firmly. Spray thin coats to avoid excessive drying times, sagging and runs. Spray C.A.B. Blender Flow-Out™ while the C.A.B. opaque aerosol is still wet, make sure to spray on both sides of the C.A.B. spray line. Clean spray button after use by turning can upside down and pressing spray button until no more product comes out.

Safety and Other Precautions: Read MSDS for precautions before using product.

MSDS: If Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000

Phone: 1-800-545-0047

Hickory, NC 28603

Fax: 1-800-721-1545

INFORMATION and LIMITED WARRANTY DISCLAIMER

To the best of our knowledge the technical data contained herein is true and accurate on the date of publication and is subject to change without prior notice. User must contact Mohawk Finishing Products to verify correctness before

specifying or ordering. No guarantee of accuracy is given or implied. We assume no responsibility for coverage, performance or injuries resulting from use. The data on this sheet represents estimated and typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We sell the products without warranty. Users assume all responsibility and liability for use. Loss or damage arising from the use of our products whether used alone or in combination with our products is the responsibility of the user. **MOHAWK FINISHING PRODUCTS MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. MOHAWK FINISHING PRODUCTS WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. The information on this sheet, as well as the products referenced herein, shall be considered "Confidential Information". Wet samples and uncured samples of these products shall be maintained as confidential and shall not be disclosed to any third party without the prior written permission of Mohawk Finishing Products.