

Mohawk

Product Data Sheet

Finishing Products, Inc.

PRIMER SEALER (FOR WOOD)

M104-0224 (BLACK), 0447 (WHITE)

AVAILABLE IN 13 OZ. AEROSOL

Product Description: Mohawk's "Primer Sealer" is designed for use on wood as a sandable undercoat for opaque lacquers. This product will provide for good adhesion of the entire topcoat system. It's ease of sandability makes for a smooth, quick drying base for opaque finishing and repair systems.

Advantages:

1. Easy to use.
2. Quick drying
3. Good adhesion.

Product Limitations:

1. Designed for interior use only.
-

Characteristics:

Weight per gallon: 7.09 ± 0.1 lbs./gal. (Black),

7.43 ± 0.1 lbs./gal. (White)

Flashpoint: < 0 F/-17.8 c

Package Viscosity: 22-25 seconds #1 Zahn cup

Dry time: Air Dry @ 72 F, 35% relative humidity

To touch: 5 minutes

To handle: 10 minutes

To sand: 20 minutes

To recoat: 20 minutes

To package: Overnight

Volatile Organic Compounds (VOC):

Not to exceed 740 grams/liter, 6.17 lbs./gal.

Spec. Gravity: 0.852 ± 0.01 (Black),

0.893 ± 0.01 (White)

Boiling Range: - 30 F/-34 c

Non Volatile (wt): 10.28 ± 0.05% (Black),

16.72 ± .05% (White)

Coverage: 100 sq. ft./gal (Black),

150 sq. ft./gal. (White)

Package Life: 3 years

Hazardous Air Pollutants: Not to exceed 0.75 ± 0.05
lb./1 lb. solids

Air Quality Data: Non-Photochemically Reactive

HMIS:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

Specifications:

Directions: SHAKE WELL BEFORE USING. Surface to be sprayed should be clean, dry, finish sanded with a wood moisture content of 6-8% maximum. For best results, use only when can temperature is between 65° F and 90°F. Use steady even strokes while spraying. Several thin coats give a better finish than one heavy coat.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551