

# Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Break-A-Way™ Glaze (13 oz. Aerosols)

M155-ALL COLORS

**Product Description:** Mohawk's Break-A-Way™ Glaze is the perfect product to easily add heavy hang up and detail accent color to ornate fine woodworking or cabinetry. Break-A-Way™ Glaze Aerosol is spray applied over a sanded sealer or finish coat and then allow drying to a chalky, powdered state that is easily removed from unwanted areas using light pressure with a synthetic abrasive pad to the desired look that you are after. Break-A-Way™ Glaze must be topcoated with a clear finish of your choice. *(Note: allow to dry 1 hour after removing excess if topcoating with a water borne finish.)*

Break-A-Way™ Glaze will help you create dramatic, clean accent lines on any shaped surface. You may never want to wipe a glaze again after trying Break-A-Way™ Glaze.

#### Advantages:

1. Convenient aerosol application
2. May be used under or over water borne finishes
3. Superior hang and build compared to solvent glazes

#### Characteristics:

Weight per gallon: 7.35 – 8.42 lbs/gal

Specific Gravity: .88 – 1.01

Flash Point: -144F/-98C

Boiling Point: Not Determined

Dry time: Air dry @ 77° F, 50% relative humidity

To Work: Allow drying to a chalky powdered state. Approx. 10 to 15 minutes

To Seal: Immediately following breaking process for conventional solvent systems.

Allow 1 hour minimum for water borne topcoats.

VOC's (coating): 4.62 to 4.82 lbs/gal (555 to 578 g/l)

VOC's (material): 4.68 to 5.03 lbs/gal (555 to 578 g/l)

VHAP's: .003 lbs VHAP's/lbs solids

MIR Value: 0.7

Solids Wt. %: 35% - 45%

Vol. %: 13% - 16%

Coverage: 212 to 260 square ft/gal @ 1 mil

Package Life: 3 years unopened

HMIS: Health – 2, Flammability – 4, Reactivity – 0, Personal Protection – X

**Directions:** SHAKE WELL BEFORE USING. Use over a sanded, sealed or finished surface. Apply as needed to areas that you want to accent, highlight or create depth to by spraying directly onto the surface. Allow to dry to a chalky state, then use a synthetic abrasive pad to remove excess until the desired look is achieved. Use a soft brush to remove unwanted dust. Break-A-Way™ Glaze must be topcoated after achieving the desired look. (Allow 1 hour dry time if topcoating with water borne finish).

**Safety Cautions:** **DANGER!** Extremely Flammable. Causes lung, eye, skin, nose and throat irritation. Harmful or fatal if swallowed. Harmful if inhaled. Vapor harmful.

**Contents:** aliphatic petroleum distillates, titanium dioxide, propane, aliphatic petroleum distillates, aluminum silicate, crystalline silica, alkyd resin solids, aluminum hydroxide.

**Other Hazards:** Causes lung, eye, skin, nose and throat irritation Overexposure may cause lungs, kidneys damage. **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Harmful or fatal if swallowed. Cancer hazard, contains crystalline silica, which can cause cancer. (Risk of cancer depends on duration and level of exposure.) Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.

**Precautions:** KEEP OUT OF REACH OF CHILDREN. Contents under pressure. Do not puncture, incinerate or discard in a compactor. Do not store above 120°F, or in direct sunlight. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Close container after each use. Wash thoroughly after handling. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Use only with adequate ventilation. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Avoid contact with eyes, skin and clothing. Vapors may cause flash fire. Keep away from heat, sparks and flame. Do not breathe dust, vapors or spray mist.

**First Aid:** If swallowed, do not induce vomiting. Get medical attention immediately. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water.

**MSDS:** See Material Safety Data Sheet (MSDS) for more information.

HAPS Compliant per US EPA guidelines.  
Contains Non-Photochemically Reactive Solvent.  
For industrial and commercial use only.

**Warning:** This product contains a chemical known to the state of California to cause cancer.

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products  
Division of RPM Wood Finishes Group, Inc.  
P O Box 22000  
Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545

Website: [www.mohawk-finishing.com](http://www.mohawk-finishing.com)