

Mohawk

Finishing Products, Inc.

Product Data Sheet

QUIK-TIP MARKER

M290-0224 (HIGH GLOSS BLACK), 0001 (TRANSPARENT WATER CLEAR), 0203 (FLAT WHITE), 0202 (HIGH GLOSS WHITE).

Product Description: Mohawk's "Quik-Tip" Marker applies a durable finish, solid color touch-up and repair in one easy operations. This product provides excellent adhesion and wear.

Advantages:

1. Solid color touch-up.
2. Durable finish.
3. High solids.
4. Quick drying.

Product Limitations:

1. Not designed for hi-heat repair.

Characteristics:

*Weight per gallon: 7.65 – 9.90 lbs./gal.

Flashpoint: 72° F/22c

*Package Viscosity: 15-18 seconds #2 Zahn cup.

Dry time: Air Dry @ 72 F, 35% Relative Humidity

To touch: 5 minutes

To handle: 10 minutes

To recoat: 15 minutes

To package: overnight

*60° Gloss Meter Readings:

Gloss 90+

Flat 15-25

Volatile Organic Compounds (VOC):

Not to exceed 745 grams/liter, 6.2 lbs/gal.

*Spec. Gravity: 0.919 – 1.19

Boiling Range: 180 F/82 c

*Non Volatile (wt.) 19.0 – 44.0%

Coverage: 230 square feet/gallon

Package life: 2 years

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: 0.75 lb. max/1 lb. solids

* Depending upon color

HMIS:

Health: 1

Flammability: 3

Reactivity: 0

Personal Protection: B

Specifications:

Directions: Surface should be clean and dry. For best results use only when marker temperature is between 65°F and 90°F. Before use, relieve pressure by depressing nib in upright position. To start flow, press pen and nib down until wet.

Safety Cautions: Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor. **USE ONLY WITH ADEQUATE VENTILATION.** Avoid contact with skin and eyes. Wash hands after using.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551