

Mohawk

Finishing Products, Inc.

Product Data Sheet

WIL-PRO PADDING FINISH

M405-200

Available in quarts

Product Description: The Mohawk padding finish is rated by the experts as #1. It quickly develops a very hard low build up repair. Lacquer topcoats may be applied immediately. Wil-Pro provides excellent clarity while providing a repair with exceptional print resistance.

Advantages:

1. Super fast-dry.
2. Very low build-up.
3. Excellent clarity.
4. No discoloration on light finishes.
5. The best for French patching

Product Limitations:

1. Designed for interior use only.

Characteristics:

Weight per gallon: 6.80 ± 0.1 lbs./gal.

Flashpoint: 8° F/-13 c

Dry time: Air Dry @ 72° F, 35% Relative Humidity

To touch: 3 minutes

To handle: 5 minutes

To recoat: 5 minutes

Spec. Gravity: 0.817 ± 0.01

Boiling Range 160 F/71c

Non Volatile (wt.) $7.5 \pm 0.3\%$

Coverage: 90 sq. ft./gal.

Package Life: 2 years

Volatile Organic Compounds (VOC): 730 grams/
Liter, 6.10 lb./gal.

Air Quality Data: Non-Photochemically Reactive

HMIS:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

Hazardous Air Pollutants: 0.24 ± 0.05 lb./1 lb. solids
lb./1 lb. solids

Specifications:

Directions: SHAKE WELL BEFORE USING. Surface should be clean and dry.

Smooth the defect with 4/0 steel wool. Use Trace cloth to form a frenching pad. Apply a small amount of Wil-Pro evenly using either the circular or straight padding motion. Use sparingly. Dries extremely fast. For lower sheen requirements topcoat with desired sheen of clear aerosol lacquer.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551