

Mohawk

Finishing Products, Inc.

Product Data Sheet

LACOSOLVENT REDUCER

M406-000

Available in quart and gallon sizes

Product Description: Mohawk's "Lacosolvent" reducer is used to lower the solids of "Lacover" and "Rapid Pad" padding finishes. This material can also be used to remove a unsatisfactory padded repair.

Advantages:

1. Easy to use.
2. Mild odor.
3. Utilized to wash down an old finish before repair.

Product Limitations:

1. Not to be used as a lacquer reducer.

Characteristics:

Weight per gallon: 6.97 ± 0.1 lbs./gal.

Flashpoint: 53° F/ 12 c

Spec. Gravity: 0.838 ± 0.01

Boiling Range 160 F/71c

Non Volatile (wt.) 0.0%

Package Life: 3 years

Volatile Organic Compounds (VOC): 840 grams/
Liter, 7.0 lb./gal.

Air Quality Data: Non-Photochemically Reactive

HMIS:

Health: 1

Flammability: 3

Reactivity: 0

Personal Protection: B

Hazardous Air Pollutants: 0.0 lb./1 lb. solids

Specifications:

Directions: To control padding with LACOVER first, add 1 to 3 dashes of LACOSOLVENT to the pad and one dash of LACOVER. The larger the surface to be padded, the more solvent should be added. If desired, LACOSOLVENT and LACOVER can be intermixed in another container. No solvent is required on padding small areas.

Safety Cautions: Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551