

# Mohawk

Finishing Products, Inc.

# Product Data Sheet

## MATCH-ALL™ STAINING LIQUID

M460- ALL COLORS

---

**Product Description:** Match-All Stain is an acrylic-based spot color repair product consisting of 11 intermixable staining colors designed to enable the user to match virtually any background color.

### Advantages:

1. Rich, true pigment colors.
  2. Fade resistant.
  3. Easy stir (or shake) in formula.
  4. Sufficient color blending time.
  5. Ability to blend a total range of color spectrum.
  6. Brushes easily.
  7. Compatible under most topcoats.
- 

### **Characteristics:**

\* Weight per gallon: 7.76 - 8.86 lbs/gal  
Flashpoint: 45F/7C  
Package Viscosity: 30-35 seconds #1 Zahn cup  
Dry time: Air dry @ 72F  
To touch: 5 minutes  
To handle: 10 minutes  
To recoat: 15 minutes  
Not to exceed Volatile Organic Compounds (VOC):  
715 GPL, 6.0 lb/gal

\* Spec. Gravity: 0.93 - 1.06  
Boiling Range: 230F/110C  
\* Non Volatile (wt): 23 - 40%  
Coverage: 300 sq. ft./gal  
Package Life: 3 years

Air Quality Data: Photochemically Reactive  
\* Hazardous Air Pollutants: 1.34 - 2.78 lb./1 lb. solids  
\* Depends upon color

### HMS:

Health: 1  
Flammability: 3  
Reactivity: 0  
Personal Protection: B

---

### **Specifications:**

**Directions:** Mix Match-All Staining Liquid before using (stir or gently shake). Use the Tinting Guide to find the color page closest to the background color. Follow the blending formula on that color page, and using the Tinting Loop, carefully measure the prescribed amount of each stain color onto the Tinting Glass.

Blend the stain colors together and hold the glass over panel to test the color. If the match is good, apply the stain to the repair area. If color needs further adjustment, tint as required.

Complete repair by replacing grain using Match-All Graining Liquid. Seal with Mohawk Sanding Sealer M102-0423 and apply Mohawk Clear Lacquer Aerosol of the proper sheen.

**Safety Cautions:** Contents are FLAMMABLE. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated.

Avoid breathing vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using.

Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 STHWY 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551