

Mohawk

Finishing Products, Inc.

Product Data Sheet

MATCH-ALL™ GRAINING LIQUID

M462- 2010 (A), 2020 (B), 2030 (C), 2040 (D)

Product Description: Match-All Graining Liquid colors are a quick drying, permanent pigment type liquid used to replace wood grain over repair areas. The graining liquid's unique characteristics enable the user to easily duplicate any type color of wood grain making repairs look natural.

Advantages:

1. Fade resistant.
 2. Intermixability of all four graining colors.
 3. Permanent grain lines that will not migrate when topcoated.
-

Characteristics:

*Weight per gallon: 7.9 - 8.5 lbs/gal

Flashpoint: 66F/19C

*Package Viscosity: 23-35 seconds #1 Zahn cup

Dry time: Air dry @ 72F

To touch: 5 minutes

To handle: 10 minutes

To recoat: 15 minutes

Volatile Organic Compounds (VOC):

Not to exceed 670 GPL, 5.6 lb/gal

*Spec. Gravity: 0.95 - 1.02

Boiling Range: 207F/97C

*Non Volatile (wt): 30 - 40%

Coverage: 400 sq. ft./gal

Package Life: 3 years

Air Quality Data: Photochemically Reactive

*Hazardous Air Pollutants: 1.10 - 1.72 lb./1 lb. solids

* Depending upon color

HMIS:

Health: 1

Flammability: 3

Reactivity: 0

Personal Protection: B

Specifications:

Directions: Be sure Match-All Graining Liquid is mixed before using (stir or gently shake). Select the color (A, B, C or D) which matches the grain of the place being repaired. Graining colors can also be intermixed to produce custom grain colors if desired.

Apply the Match-All Graining Liquid color over the Match-All stained repair using the long bristled graining brush. Duplicate the surrounding grain as closely as possible. When graining is complete, apply a coat of aerosol Sanding Sealer.

Finish the repair with a coat of your favorite Mohawk Clear Aerosol Lacquer of the proper sheen.

Safety Cautions: Contents are FLAMMABLE. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated.
Avoid breathing vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using.
Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:
Mohawk Finishing Products, Inc.
4715 STHWY 30
Amsterdam, NY 12010-7417
Phone: 518-843-1380
Fax: 518-842-3551