

# Mohawk

Finishing Products, Inc.

# Product Data Sheet

## BLEACHTONE PURE WHITE

M550- 202

AVAILABLE IN GALLONS

---

**Product Description:** Mohawk Bleachtone is made from man-made pigments in a synthetic base. Semi-transparent in nature, it will not give a painted-out look when properly used. Bleachtone sprayed on walnut, mahogany, pecan, oak or any dark wood lightens color, but does not block out the grain. Gives same results formerly obtained only by double bleaching. Use in combination with Nu-Glaze II to obtain beautiful hand detailed finishes of fine furniture. Bleachtone is the product to use to attain soft, subdued mahogany or the popular provincial finishes.

### Advantages:

1. Pigments are nontoxic.
2. Uniformity of color.
3. When properly applied, fine grain patterns are clearly visible.
4. Seal coat can be applied over stain coat after 10 minutes of dry time.

### Product Limitations:

1. If water based topcoat is used, stain must be thoroughly dry (overnight).
2. Product must be topcoated to attain wearing qualities.

---

### **Characteristics:**

Weight per gallon: 7.90 ± 0.1 lbs/gal

Flashpoint: 4F/-16C

Package Viscosity: 22-24 seconds #1 Zahn cup

Dry time: Air dry @ 72F

To touch: 5 minutes

To handle: 10 minutes

To recoat: 15 minutes

Volatile Organic Compounds (VOC):

Not to exceed 821 GPL, 6.85 lb/gal

Spec. Gravity: 0.95 ± 0.01

Boiling Range: 132F/56C

Non Volatile (wt): 14.85 ± 0.5%

Coverage: 66 sq. ft./gal

Package Life: 3 years

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: 0.18 ± 0.05/1 lb. solids

### HMIS:

Health: 1

Flammability: 4

Reactivity: 0

Personal Protection: B

## **Specifications:**

**Directions:** Concentrated - use only Bleachtone Reducer M550-2227 to thin. A reduction of 1 to 1 by volume is proper for most finish jobs.

For spray application only. Use low air pressure - 15 to 20 lbs. Do not dry spray. Apply even, moderately wet coat. Do not double coat.

Bleachtone may be tinted with Base Concentrates for desired color at 2 oz. Base Concentrate per gallon of Bleachtone.

Dry time is 10 minutes to seal.

**Safety Cautions:** Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated.

Avoid breathing vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using.

Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 STHWY 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551