

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

DuraCoat™ II Catalyst

M612-301

Available in 3.2 fluid ounce & 16 fluid ounce containers.

Product Description: Mohawk DuraCoat™ II Catalyst is specially formulated for use in Duracoat™ II Post-Catalyzed Products including clear topcoats, sealer and white lacquer.

Characteristics:

Weight per gallon: 6.69 lbs/gal*

VOC's (coating): .188 lbs/gal (22.6 g/l)*

VOC's (material): .006 lbs/gal (.67 g/l)*

VHAP's: 0.0lbs VHAP's/lb solids*

Package life: 3 year

* All values theoretical; not intended to be exact QC specifications.

HMIS: Health – 2, Flammability – 3, Reactivity – 0, Personal Protection - X

Specifications:

Directions: DuraCoat™ II Catalyst is packaged in 3.2 oz containers for single gallon (125 oz.) and 16 oz. containers for 5 gallon pails (625 oz.). Add entire contents of the proper size, pre-measured bottle of DuraCoat™ II Catalyst to catalyze the entire container of DuraCoat™ II Post-Catalyzed clear or white topcoats. Stir material while adding catalyst and continue to stir until thoroughly mixed. Material is now ready for spraying.

Notes: The entire container of DuraCoat™ II Post-Catalyzed clear or white topcoats must be catalyzed at once. Do not catalyze partial amounts. Attempting to catalyze partial amounts may result in poor performance of the product.

Safety and Other Precautions: Read MSDS for precautions before using product.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000

Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545