

# Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

## Product Data Sheet

### Conversion Varnish Catalyst 275 VOC

#### M612-701

Available in 4 fluid ounce & 20 fluid ounce containers.

**Product Description:** Mohawk Catalyst 275 VOC is specially formulated for use in Ultra Clear™ Conversion Varnish 275 VOC and Ultra White™ Conversion Varnish 275 VOC.

#### Characteristics:

Weight per gallon: 8.26 lbs/gal

VHAP's: 0.0lbs VHAP's/lb solids

VOC's (coating): 5.94 lbs/gal (594 g/l)

Package life: 3 years

VOC's (material): 5.94 lbs/gal (594 g/l)

HMIS: Health – 2, Flammability – 3, Reactivity – 0, Personal Protection - X

#### Specifications:

**Directions:** Conversion Varnish Catalyst (M612-701) is designed specifically for use in Ultra™ Clear Conversion Varnish 275 VOC products (M612-28XX), Ultra™ Clear Conversion Varnish Sealer (M612-2800) and Ultra™ White Conversion Varnish (M612-27XX). While stirring, slowly add 4 ounces per gallon of Conversion Varnish Catalyst (M612-701) into the coating. Continue to stir until thoroughly mixed. Allow the catalyzed coating to sit for a minimum of 15 minutes before application.

**Safety and Other Precautions:** Read MSDS for precautions before using product.

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000

Phone: 1-800-545-0047

Hickory, NC 28603

Fax: 1-800-721-1545