

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

BoothCoat™ Spray Booth Protector

M617-0017

Available in 1 gallon

Product Description: BoothCoat™ has been designed to coat the interior of spray booths for easy cleaning and disposal of over spray deposited during finishing operations. BoothCoat™ is a spray applied coating that is supplied ready to use. Once the spray booth is ready for cleaning you simply peel away the BoothCoat™ and contamination, then dispose of it in an appropriate solid hazardous waste container.

Characteristics:

Weight per gallon: 7.47 lbs/gal

Solids % (wt): 23.88

Solids % (vol): 15.76

Package viscosity: 42-44 seconds, # 4 Ford cup

Dry time: Air dry to touch in 30 minutes at 77 deg. F and 45% relative humidity.

VOC's (coating): 3.74 lbs/gal (449.64 g/l)

VOC's (material): 1.21 lbs/gal (145.02 g/l)

VHAP's: 0.23 lbs VHAP's/lb solids

Package life: 2 years

HMIS: Health – 2, Flammability – 3, Reactivity – 0, Personal Protection - X

Specifications:

Application Directions: Stir product thoroughly after opening. BoothCoat™ Spray Booth Protector is ready to spray and should be applied in multiple light coats. 3-4 coats are recommended for best results. Equipment can be cleaned with Lacquer Reducer 2255 (M650-010).

Removal Directions: Removing Mohawk BoothCoat™ Spray Booth Protector is easy. Simply peel it off and re-apply following the application directions above. Dispose of waste according to local and state regulations.

Note: Spray booths should be cleaned often to insure a safe, bright and clean environment that is suitable for spraying. Mohawk BoothCoat™ Spray Booth Protector should become part of a regular clean up routine that takes place at least once a quarter or as needed.

All products should be stirred properly before being used and also continuously agitated while in use to insure product consistency from start to finish. Mixing with other products or finish systems is not recommended. Mohawk Finishing Products will not be held liable for finish failure resulting from mixing products or systems.

Safety Cautions: Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes skin, nose and throat irritation. May be harmful if absorbed through skin. Harmful or fatal if swallowed.

Contains: acetone, vinyl chloride acetate copolymer, n-butyl acetate, toluene, diisononyl phthalate, vinyl chloride

Notice: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Precautionary Measures: Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor-mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes, on skin or clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN.**

First Aid Measures: In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately; for skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately.

Special Instructions: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

This product contains chemicals known to the state of California to cause cancer and birth defects, or other reproductive harm.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products
Division of RPM Wood Finishes Group, Inc.
P O Box 22000
Hickory, NC 28603

Phone: 1-800-545-0047

Fax: 1-800-721-1545