

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

Product Data Sheet

Lacquer Reducer 2255

M650-010

Available in 1 gallon, 5 gallons

Product Description: Lacquer Reducer 2255 is formulated with only the highest quality solvents. The special blend helps prevent orange peel and helps provide good flow out. Recommended for use with all Mohawk nitrocellulose, pre-catalyzed lacquer and post-catalyzed lacquer coatings.

Advantages:

1. Enhance flow & atomization
2. Reduce solids content to control build
3. Special blend provides proper evaporation rate

Characteristics:

Weight per gallon: 6.62 lbs

Solids % (wt): 0.0

Solids % (vol): 0.0

VOC's (coating): 6.61 lbs/gal (794.0 g/l)

VOC's (material): 5.68 lbs/gal (682.6 g/l)

VHAP's: .071% by weight (0.47 lbs/gal)

Package life: 3 years

All values theoretical; not intended to be exact QC specifications.

HMIS: Health – 2, Flammability – 3, Reactivity – 0, Personal Protection - X

Directions: Adjust reductions to suit conditions, viscosity requirements, equipment and manufacture's suggestions.

Note: Reducers are used to control viscosity of coatings, which lowers solids content. If additional open time is needed then a retarder solvent should be considered.

Safety and Other Precautions: Read MSDS for precautions before using product.

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products

Division of RPM Wood Finishes Group, Inc.

P.O. Box 22000

Phone: 1-800-545-0047

Hickory, NC 28603

Fax: 1-800-721-1545