

Mohawk

Finishing Products, Inc.

Product Data Sheet

FLAT LUBE™

M720- 130

AVAILABLE IN QUARTS

Product Description: Mohawk Flat Lube is a rubbing lubricant in paste form. Flat Lube is used in conjunction with water and steel wool to produce a flattened sheen. Flat Lube is recommended for dulling a french polish or lacquer finish.

Advantages:

1. Use on spot repairs to match a surrounding sheen.
 2. Eliminates hairline scratches.
 3. Ideal for oil walnut finishes.
-

Characteristics:

Weight per gallon: 7.91 ± 0.1 lbs/gal
Flashpoint: None Observed
Package Viscosity: N/A

Volatile Organic Compounds (VOC):
0 GPL, 0.0 lb/gal

Spec. Gravity: $.95 \pm 0.01$

Boiling Range: N/A

Coverage: 700 sq. ft./gal

Package Life: 2 years

Air Quality Data: Non-Photochemically Reactive
Hazardous Air Pollutants: 0.00 lb./ 1 lb. solids

HMIS:

Health: 1

Flammability: 0

Reactivity: 0

Personal Protection: B

Specifications:

Directions: Apply with a steel wool pad to an existing finish. Steel wool in grades of 1/0 and 2/0 is recommended to dull the sheen rapidly without fear of damage.

After the surface has been rubbed down, the Flat Lube should remain on the surface a few minutes prior to washing down with clear water to provide a good rubbed effect finish. The grade of steel wool and degree of rubbing can be modified to achieve the desired luster.

Safety Cautions: Contents are NON-FLAMMABLE. Avoid contact with skin and eyes. Wash hands after using.

Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 STHWY 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551