

Mohawk

Finishing Products, Inc.

Product Data Sheet

RUBBING COMPOUND LEVEL I (LOW SHEEN)

M730-100 (NEUTRAL), 400 (BLACK)

Available in quarts

Product Description: The Mohawk Level I Rubbing Compound will produce a low final sheen on coatings such as lacquer, shellac, varnish, etc. This material is also suitable for the removal of overspray and minor surface imperfections.

Advantages:

1. Choice of two colors.
2. Semi Paste form.
3. Quick clean-up.

Product Limitations:

1. For low sheen development.
-

Characteristics:

Weight per gallon: 11.85 ± 0.1 lbs./gal.

Flashpoint: 107 F/42 c

Spec. Gravity: 1.43 ± 0.01

Boiling Range: 320 F/160 c

Non Volatile (wt): 63.5 ± 1.0%

Package Life: 2 years

Coverage: 400 square feet/gallon

Volatile Organic Compounds (VOC) 450 grams/
Liter, 3.75 lbs./gal.

Hazardous Air Pollutants: 0.04 ± 0.005 lb./1 lb.
solids

Air Quality Data: Photochemically Reactive

HMIS:

Health: 1

Flammability: 2

Reactivity: 0

Personal Protection: B

Specifications:

Directions: Surface should be clean and dry. A fine, semi-paste compound containing fine cutting abrasives. Can be applied with cloth, burlap or felt to rub down all types of finishes such as shellac, lacquer and synthetic finishes. Rubbing Compound can be used for removing defects in topcoats.

Safety Cautions: Contents are **EXTREMELY FLAMMABLE**. Vapors may ignite **EXPLOSIVELY**. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. **USE ONLY ADEQUATE VENTILATION**. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

MSDS: If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 STHWY 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551