

# Mohawk

Finishing Products, Inc.

# Product Data Sheet

## RUB CUT OIL

**M740-100**

Available in gallons

**Product Description:** Mohawk's "Rub Cut Oil" is the lubricant of choice for use with abrasive papers, pumice, or rottenstone. This product will speed-up the rubbing, leveling, and cutting down of a finish to help develop a more even end result.

### Advantages:

1. Easy to use.
2. Will not clog or dry out.
3. Saves time and effort.
4. Suitable for all finishes.

### Product Limitations:

1. Not for use with direct food contact.

### **Characteristics:**

Weight per gallon:  $7.17 \pm 0.1$  lbs./gal.

Flashpoint: 129 F/54 c

Package Viscosity: 16-18 seconds #2 Zahn cup

Volatile Organic Compounds (VOC): Not to exceed 172 grams/liter, 1.43 lbs./gal.

Spec. Gravity:  $0.862 \pm 0.01$

Non Volatile (wt.)  $80.0 \pm 1\%$

Package Life: 3 years

Boiling Range: 354 F/179 c

Coverage: 600 square feet/gallon

Air Quality Data: Non-Photochemically Reactive

Hazardous Air Pollutants: 0.0 lb./1 lb. Solids

### HMIS:

Health: 1

Flammability: 2

Reactivity: 0

Personal Protection: B

**Specifications:**

**Directions:** SHAKE WELL BEFORE USING. Surface should be clean and dry. For best results, use only when can temperature is between 65° F and 90° F. Clean-up with Mineral Spirits.

**Safety Cautions:** Contents are EXTREMELY FLAMMABLE. Vapors may ignite EXPLOSIVELY. Keep away from heat, sparks and open flame. During use and until all vapors are gone, keep area well ventilated. Avoid breathing of vapor and spray mist. USE ONLY WITH ADEQUATE VENTILATION. Avoid contact with skin and eyes. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

KEEP OUT OF REACH OF CHILDREN

**MSDS:** If Material Safety Data Sheet is required, contact:

Mohawk Finishing Products, Inc.

4715 State Highway 30

Amsterdam, NY 12010-7417

Phone: 518-843-1380

Fax: 518-842-3551